

## 101 Dumps

### Application Delivery Fundamentals

<https://www.certleader.com/101-dumps.html>



#### NEW QUESTION 1

TI SSSL prides which functionary when a web browser connects to web site using the HTTPS protocol?

- A. delivers secure communication over a network connection
- B. prevents the web server from being compromised
- C. protects network packets from interception by intermediaries
- D. stop the web browser from automatically downloading malware

**Answer:** A

#### NEW QUESTION 2

A client receives all of the expected data from a server and sends a FIN packet signaling the end of communication. What will the server do when it receives the FIN Packet from the client?

- A. send a SYN packet
- B. send an RST packet
- C. Send both FIN and RST packets
- D. send an ACK Packet

**Answer:** D

#### Explanation:

<https://www.geeksforgeeks.org/computer-networ-tcp-connection-termination/>

#### NEW QUESTION 3

A load balancing decision needs to be made based on custom a What is the most appropriate F5 feature (or this purpose?

- A. iApps
- B. Scale
- C. iControl
- D. iRules

**Answer:** D

#### NEW QUESTION 4

Which OSI layer provides reliable transmission of frames between adjacent nodes and is built on top of the provides reliable transmission of frames adjacent nodes and is built on top of the Physical layer?

- A. Data link
- B. Transport
- C. Network
- D. Application

**Answer:** A

#### NEW QUESTION 5

Which high availability feature allows two different BIG-IP devices to use the MAC address for the same server IP?

- A. HSRP virtual MAC address
- B. Device group
- C. Sync- failover
- D. MAC masquerade

**Answer:** D

#### NEW QUESTION 6

Which HTTP response code is returned when a web server requires authentication to access a resource?

- A. 500
- B. 401
- C. 302
- D. 100

**Answer:** B

#### NEW QUESTION 7

Which function does the Presentation Layer provide?

- A. translation and encryption
- B. transmission over a medium
- C. internetworking capabilities
- D. access to available resources

**Answer:** A

**NEW QUESTION 8**

An administrator finds a new vulnerability in a web application and needs to rapidly mitigate the threat. Which F5 feature provides this functionality?

- A. iCall
- B. iRules
- C. iSession
- D. iControl

**Answer:** B

**NEW QUESTION 9**

An administrator takes a capture of five Traffic using tcpdump. The administrator notices that different ephemeral port numbers are architecture does this indicate?

- A. packet-based architecture
- B. full proxy architecture
- C. hub and spoke architecture
- D. ring network architecture

**Answer:** B

**NEW QUESTION 10**

A Network Administrator needs a new networking device can perform NAT to connect several devices on a computer network. What is the most appropriate device for this requirement?

- A. Switch
- B. Router
- C. Bridges
- D. Hub

**Answer:** B

**NEW QUESTION 10**

VLAN test-vlan" is configured on interface 1 1 instead of interface 1.2. Which TMSH command should be used to correct this issue?

- A. modify /net test vlan interfaces {1.2}
- B. modify /net test-vlan interfaces replace all with {1 2}
- C. modify /net vlan test-vlan interfaces replace all with {12}
- D. modify /net sian test-vlan interfaces {1 2}

**Answer:** C

**NEW QUESTION 11**

In which scenario is a full proxy TCP connection required?

- A. TCP routing
- B. IPv4 to IPv6 gateway
- C. UDP routing
- D. UDP to ICMP gateway

**Answer:** B

**NEW QUESTION 14**

User A and User B's workload are on the same VLAN, but connected through a transparent layer 2 bridge in use B's ARP table. Which MAC address is reported for user A's workstation?

- A. The physical port MAC address on the bridge for user A's workstation
- B. The MAC address of the 12 bridge
- C. The MAC address of User A's workstation
- D. The physical port MAC address on the bridge for user B's workstation

**Answer:** D

**NEW QUESTION 16**

Ethernet frame FCS errors occur when which calculation fails?

- A. FSCM
- B. CRC
- C. CSR
- D. HSTS

**Answer:** B

**NEW QUESTION 18**

In wh.ch layer of the OSI model is the data transported in the form of a packet?

- A. Transport
- B. Session
- C. Network
- D. Presentation

**Answer:** C

**NEW QUESTION 22**

A BIG IP Administrator is trying to reach the internal web server from a workstation

- \* The workstation has a MAC address of 00:00 00 00 00 01 and an IP address of 192. 168. 0. 1
  - \* An internal web server has a MAC address of 00 00 00 00 00 02 and an IP address of 10. 10. 1. 1
  - \* The workstation's default gateway has a MAC address of 00 00 00 00 00 03 and IP address of 192 168 0 254
- What is the destination hardware address of the outbound packet when it leaves the workstation?

- A. 00:00.00:00:00:01
- B. 00:00:00 :00:00:00
- C. 00:00:00:00:00:03
- D. 00:00:00:00:00 02

**Answer:** C

**NEW QUESTION 23**

A user fails to provide credentials when requesting a web resource that requires authentication. Which HTTP response code does the server send?

- A. HTTP 200
- B. HTTP 302
- C. HTTP 401
- D. HTTP 502

**Answer:** C

**Explanation:**

<https://httpstatuses.com/401>

**NEW QUESTION 28**

An administrator needs to restore the BIG-IP configuration from a UCS file. In which section in the BIG IP Configuration utility is this task performed?

- A. System > Archives
- B. System > Services > Backup
- C. System > Backup
- D. System > File Management

**Answer:** A

**NEW QUESTION 32**

Which technology can be used on a BIG-IP device to accelerate the delivery of the same content to multiple users?

- A. persistence
- B. SSL offloading
- C. Compression
- D. caching

**Answer:** D

**NEW QUESTION 35**

An administrator configures a default gateway for the host. What is the purpose of a default gateway?

- A. to replace the destination IP address with the default gateway
- B. to pass all traffic to the default gateway
- C. to forward packets to remote networks
- D. to populate the ARP table

**Answer:** C

**NEW QUESTION 40**

An administrator's security policy defines allowed URLs, file types, and parameter values. Which security model is the administrator using?

- A. negative security model
- B. Closed security model
- C. positive Security model
- D. ACL Security model

**Answer:** C

**Explanation:**

[https://www.owasp.org/index.php/Positive\\_security\\_model](https://www.owasp.org/index.php/Positive_security_model)

**NEW QUESTION 45**

in which scenario is a full proxy TCP connection required?

- A. when SSL offloading is used
- B. when Traffic is routed
- C. when administrators manage the servers directly
- D. when 3 server responds directly to the client

**Answer:** A

**NEW QUESTION 49**

A BIG IP Administrator wants to add a new VLAN (VLAN 40) to an LACP trunk (named LACP01) connected to the BIG IP device, Multiple other VLANs exist on LACP01. Which TMSH command should the BIG IP Administrator issue to add the new VLAN to the existing LAC?

A BIG IP Administrator wants to add a new VLAN (VLAN 40) to an LACP trunk (named IACP01) connected to the BIG IP device Multiple other VLANs exist on LACP01. Which TMSH command should the BIG IP Administrator issue to add the new VLAN to the existing LAC?

- A. create net vlan VIAN40 (interfaces replace all with {LACP01 (untagged } } lag 40 )
- B. create net vian VLAN40 (interfaces add { LACP01 {tagged} tag JO J
- C. create net vian VLAN40 {interfaces add ( LACP01 {untagged)) tag 40}
- D. create net wan VLAN40 {interfaces replace all with {LACP01 {tagged }} lag 40 }

**Answer:** B

**Explanation:**

Tagged" VLAN is how F5 refers to a VIAN within an 802.1q trunk. The fact that it is an FS trunk' or an LACP/etherchannel link only changeshowthe interface is referred to in the command.

**NEW QUESTION 52**

An administrator needs to selectively compress HTTP traffic based on geographical location Which FS Feature should the administrator use?

- A. One Connect
- B. iRules
- C. SPDY profile
- D. iSessions

**Answer:** B

**NEW QUESTION 54**

An organization needs to protect its data center from layer three-based and layer four-based exploits. Which F5 product provides this functionality

- A. AFM
- B. ASM
- C. GTM
- D. APM

**Answer:** A

**Explanation:**

<https://www.f5.com/producrs/security/advanced-firewall-manager>

**NEW QUESTION 55**

A BIG-IP Administrator needs to create a route to send traffic destined to 10.1.1 1 to another router with an address of 192 168 1 1 Which TMSH command should the administrator use?

- A. create/net route 10. 11. 1/32 gw 192 168. 1. 1
- B. create met route 192 168. 1. 1/32 gw 10. 11. 1
- C. add met route 192. 168. 1. 1/32 gw 10. 1. 1. 1
- D. add inet route 10.11.1/32 gw 192. 168.1.1

**Answer:** A

**NEW QUESTION 60**

There is no SFP plugged into the port.

Port	Interface	Bytes In	Bytes Out	Pkts In	Pkts Out	Drops	Errs	Media
1-1	up	10,80	110,9M	10,8M	220,5K	22,1M	0	1000T-1D
1-2	down	0	0	0	0	0	0	none
1-3	down	0	0	0	0	0	0	none
1-4	down	0	0	0	0	0	0	none
1-5	down	0	0	0	0	0	0	none
1-6	down	0	0	0	0	0	0	none
1-7	down	0	0	0	0	0	0	none
1-8	down	0	0	0	0	0	0	none
2-1	miss	0	0	0	0	0	0	none
2-2	miss	0	0	0	0	0	0	none
2-3	miss	0	0	0	0	0	0	none
2-4	miss	0	0	0	0	0	0	none
total	up	220,20	47,40	241,9M	20,2M	0	0	none

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

There is no SFP plugged into the port.

**NEW QUESTION 65**

An administrator wants to insert per-session data in a users browser so that user requests are directed to the same session. Which session persistence method should the administrator use?

- A. SSL persistence
- B. Source address persistence
- C. destination address persistence
- D. cookie persistence

**Answer:** D

**Explanation:**

<https://support.f5.com/csp/article/K83419154>

**NEW QUESTION 66**

An application uses a proprietary protocol running over TCP. Which F5 BIG-IP feature should the administrator use to modify the protocol?

- A. SPDY
- B. rewrite profile
- C. TCP profile
- D. iRules

**Answer:** D

**NEW QUESTION 70**

Which function does a caching profile provide on the BIG-IP server?

- A. caches client IP addresses to improve response times
- B. caches HTTP headers to improve server load times.
- C. caches selected pool members to improve load balancing times.
- D. caches data for reuse to cut down on transfer time for future requests

**Answer:** D

**Explanation:**

The ltmcache profile is a memory cache of data from pool members.

**NEW QUESTION 73**

An administrator needs to prepare change control documents for operations staff. To reduce possible errors, the administrator killed the number of default configuration options. Which F5 feature is intended to help with this task?

- A. icontrol



- B. iCatl
- C. iApp
- D. iRules

**Answer:** A

**Explanation:**

<https://devcentral.f5.com/iconcontrol>

**NEW QUESTION 76**

When is the server also a client?

- A. during a passive FTP session
- B. during an active FTP session
- C. While receiving email
- D. While uploading files

**Answer:** B

**NEW QUESTION 78**

in which scenario is a full proxy TCP connection required?

- A. when compression is actuated
- B. When Source NAT configured
- C. when a virtual server is configured
- D. When Source IP persistence is required

**Answer:** A

**Explanation:**

<https://devcentral.f5.com/articles/the-full-proxy-data-center-architecture>

**NEW QUESTION 82**

An Administrator enables HTTP keep alive. How does this affect the network?

- A. HTTP connections will remain open longer
- B. Fewer TCP connections will need to be opened
- C. HTTP connections will close when the keep-alive times out
- D. More TCP connections will need to be opened

**Answer:** B

**Explanation:**

<https://en.wikipedia.org/wiki/HTTPpersistentconnection>

**NEW QUESTION 85**

An administrator is designing a remote host connection using an ICMP based network troubleshooting utility and receive an ICMP error diagram with the following error code.

\* 11. Times exceeded What does this mean?

- A. A faulty router on the network is unable to process the packet in a timely manner
- B. A switch on the network the frame due to an incorrect checksum
- C. The TTL field of the IP header was set to 255. and this was consequently dropped by a router
- D. The TTL field of the IP header was decremented to 0. and this was consequently dropped by a router

**Answer:** D

**NEW QUESTION 89**

Which HTTP response code indicates an OK status?

- A. 302
- B. 404
- C. 200
- D. 100

**Answer:** C

**NEW QUESTION 93**

A company deploys F5 load balancers to manage number of secure applications. The company needs to centrally manage certificates. Which F5 product provides this functionality?

- A. BIG IQ
- B. GTW
- C. iHeath
- D. LTM

**Answer:** A

#### NEW QUESTION 95


Which of the following is a valid IP address and prefix length?

- A. 192. 168.:0 177/25
- B. 192 168:0. 129/25
- C. 192.168:0 128/25
- D. 192 168 :0 255/25

**Answer:** B

#### NEW QUESTION 98

An administrator is having a connectivity issue with a server in the same network. Upon checking with the command `arp -a` on a Windows machine, the two outputs are taken on a 1 minute interval "hat is likely causing this issue?



Internet Address	Physical Address	Type
192.168.56.101	08-00-27-21-fb-45	dynamic
192.168.56.255	ff-ff-ff-ff-ff-ff	static

Internet Address	Physical Address	Type
192.168.56.101	08-00-27-74-17-01	dynamic
192.168.56.255	ff-ff-ff-ff-ff-ff	static

- A. Interface down
- B. MAC address conflict
- C. No route available
- D. IP address conflict

**Answer:** D

#### NEW QUESTION 100

What does the 5XX group of HTTP status codes indicate?

- A. Redirection
- B. Successful
- C. Client Error
- D. Server Error

**Answer:** D

#### NEW QUESTION 105

The BIG-IP device has the status of interface 2 1 as DOWN The BIG-IP Administrator. What is the likely reason for the status of the interface to be DOWN?

- A. The interface 3/2/1 is UP on switch
- B. The interface 2.1 is disabled on the BIG-IP device
- C. The interface 3/2/1 is DOWN on switch
- D. The interface 2. 1 is unpopulated on the BIG-IP device

**Answer:** C

#### NEW QUESTION 106

A server is operating on the network 10.100/24. The BIG-IP device is operating on the 192.168.0.0/24 net. What is required to enable the several and BIG-IP device to communicate properly?

- A. Firewall
- B. Switch
- C. Router
- D. Hub

**Answer:** C

#### NEW QUESTION 111

A BIG-IP Administrator has a cluster of devices.

What should the administrator do after creating a new Virtual Server on device 1?

- A. synchronize the settings of device 1 to the group
- B. create a new cluster on device 1
- C. create the new virtual server on device 2
- D. synchronize the settings of the group to device 1



**Answer:** A

**NEW QUESTION 112**

A BIG-IP Administrator needs to configure a network to separate traffic into three different VLANs using a single port on the BIG-IP device. What means should be used to allow this?

- A. LACP link aggregation
- B. Multiple MAC registration Protocol
- C. 802.1Q VLAN tagging
- D. Port Spanning

**Answer:** C

**NEW QUESTION 117**

A web administrator has added content to a web application, but users are unable to access the new content. What could be preventing them from accessing the content?

- A. The webapp uses negative security, and the attack signature is using an invalid regular expression
- B. The webapp uses positive security
- C. and the database has not been updated
- D. The webapp uses positive security, and the new content has not been defined as allowed behavior
- E. The webapp uses negative security
- F. and the denial of service signatures have not been updated

**Answer:** C

**NEW QUESTION 122**

In a fully proxy architecture, what is considered the client in the server-side communications?

- A. the ADC
- B. the switch
- C. the server
- D. the client workstation

**Answer:** A

**NEW QUESTION 127**

What tool should the BIG-IP Administrator use to view the status of all virtual servers and associated resources in one place?

- A. System performance
- B. Network Map
- C. Pool statistics
- D. Virtual server statistics

**Answer:** B

**NEW QUESTION 129**

An administrator needs a data format that supports authentication against an external security domain. The data format must support SSO. Which data format should the administrator choose?

- A. AAA
- B. Kerberos
- C. SAML
- D. EAP

**Answer:** C

**NEW QUESTION 133**

AD VLAN must be created with an 802.1Q tag of 705 on interface 11. What is the proper TSH command to create this new VLAN on the BIG-IP?

- A. Create net wan internal interfaces add {1 1 (tagged)} tag 706
- B. Create net vlan internal trunk add (11 {tagged})
- C. add net vlan internal interfaces add (11) tag 705
- D. add / net vlan internal trunk add {1 1 (tagged)} tag 705

**Answer:** A

**NEW QUESTION 137**

Layer 2 mapping information is announced by an interface without receiving a request for the mapping first. Which term describes this event?

- A. ICMP
- B. STP
- C. gratuitous ARP
- D. ARP

**Answer:** C

**NEW QUESTION 138**

Which protocol data unit (POU) is associated with the OSI model's Network layer

- A. Segment
- B. Datagram
- C. Bit
- D. Frame

**Answer:** B

**NEW QUESTION 140**

Pool A has three members. Why is the pool up?



- A. Heaton monitoring is enabled on only one member
- B. One member has a successful health monitor
- C. Member status is determined by volume of traffic
- D. There is no health monitoring

**Answer:** B

**NEW QUESTION 142**

How does file caching affect the web application?

- A. It reduces the load on the web application
- B. It speeds up traffic to the web application
- C. It slows traffic to the web application
- D. It increases the load on the web application

**Answer:** A

**NEW QUESTION 144**

Which device group type allows a BIG IP system to automatically become active in the event that the current active system fails?

- A. Sync-active
- B. sync-failover
- C. sync-standby
- D. sync-only

**Answer:** B

**Explanation:**

The sync-failover group allows for failover of a traffic group. The sync-only will synchronize ASM profiles and some other device information but does not deal with traffic groups

**NEW QUESTION 146**

What is used to resolve IP address to MAC address mappings?

- A. DHCP
- B. ARP
- C. DNS
- D. ICMP

**Answer:** B

**Explanation:**

[https://enWikipedia.org/wiki/Address\\_Resolution\\_Protocol](https://enWikipedia.org/wiki/Address_Resolution_Protocol)

**NEW QUESTION 148**

At which layer of the OSJ model does the DNS resolution process occur?

- A. Layer 7
- B. Layer 4
- C. Layer 2
- D. Layer 3

**Answer:** A

**NEW QUESTION 149**

A company needs to use a custom value when making persistence decisions. Which F5 product provides this functionality?

- A. iControl
- B. (Rules
- C. IApps
- D. (Health

**Answer:** B

**NEW QUESTION 153**

A BIG IP Administrator need to perform a packet capture and identify the source IP that is connecting to the Virtual Server. Which utility should the administrator use on the BIG IP device?

- A. leinel
- B. traceroute
- C. ping
- D. tcpdump

**Answer:** D

**NEW QUESTION 155**

in which scenario is a full proxy TCP connection required?

- A. when SIP UP P load balancing is defined
- B. when DNS load balancing is configured
- C. when compression is enabled
- D. when layer 3 load balancing is configured

**Answer:** C

**NEW QUESTION 157**

A BIG-IP Administrator needs to open a case with F5 Support for a specific issue with an existing HA pair of BIG-IP platform. What should be uploaded to iHealth prior to opening the case to expedite processing of the support case?

- A. UCS file
- B. SCF filo
- C. tcpdump file
- D. Qkview file

**Answer:** D

**NEW QUESTION 162**

An administrator needs to connect a new device to a switched network. The interconnect must be both redundant and combined bandwidth than a single link. Which low-level protocol will help facilitate this?

- A. Link Aggregation Control Protocol (LACP)
- B. Link Allocation & Configuration Protocol (LACP)
- C. Link Local Distribution Protocol (LLDP)
- D. Link Layer Discovery Protocol (LDP)

**Answer:** A

**NEW QUESTION 165**

In which scenario is a packet forwarding architecture required?

- A. when HTTP header must be modified
- B. when cookie persistency is demanded
- C. when the server responds directly to the client
- D. when the number of TCP connections on the server should be reduced

**Answer:** C

**NEW QUESTION 167**

An administrator is updating private keys used for SSL encryption from 1024 to 2048 bits. Which possible effect should the administrator consider when performing this activity?

- A. The larger Key size will increase processing requirements
- B. Some hardware will NOT support the 2048 key
- C. Some certificate authorities will NOT support the 2048 key
- D. The larger key sire will increase private key installation complexity


**Answer:** A

**NEW QUESTION 168**


Web application <http://www.example.com> at 10.10.1.1.10 is unresponsive.

A recent change installed new firewalls in the network. Which command should be used to locate where data loss has occurred within the network?


A)




B)



C)



D)



- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer:** C

**Explanation:**

Traceroute attempts to send ICMP-packets that expire further down the network and determine if a network device is responding or allowing traffic through.

**NEW QUESTION 170**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 101 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/101-dumps.html>