



# CompTIA

## Exam Questions N10-008

CompTIA Network+Exam

#### NEW QUESTION 1

- (Exam Topic 1)

An engineer is configuring redundant network links between switches. Which of the following should the engineer enable to prevent network stability issues?

- A. 802.1Q
- B. STP
- C. Flow control
- D. CSMA/CD

**Answer: B**

#### NEW QUESTION 2

- (Exam Topic 1)

A network administrator is designing a new datacenter in a different region that will need to communicate to the old datacenter with a secure connection. Which of the following access methods would provide the BEST security for this new datacenter?

- A. Virtual network computing
- B. Secure Socket Shell
- C. In-band connection
- D. Site-to-site VPN

**Answer: D**

#### NEW QUESTION 3

- (Exam Topic 1)

A network administrator is installing a wireless network at a client's office. Which of the following IEEE 802.11 standards would be BEST to use for multiple simultaneous client access?

- A. CDMA
- B. CSMA/CD
- C. CSMA/CA
- D. GSM

**Answer: A**

#### NEW QUESTION 4

- (Exam Topic 1)

The following configuration is applied to a DHCP server connected to a VPN concentrator:

```
IP address:      10.0.0.1
Subnet mask:     255.255.255.0
Gateway:        10.0.0.254
```

There are 300 non-concurrent sales representatives who log in for one hour a day to upload reports, and 252 of these representatives are able to connect to the VPN without any issues. The remaining sales representatives cannot connect to the VPN over the course of the day. Which of the following can be done to resolve the issue without utilizing additional resources?

- A. Decrease the lease duration
- B. Reboot the DHCP server
- C. Install a new VPN concentrator
- D. Configure a new router

**Answer: A**

#### NEW QUESTION 5

- (Exam Topic 1)

Which of the following is the physical topology for an Ethernet LAN?

- A. Bus
- B. Ring
- C. Mesh
- D. Star

**Answer: D**

#### NEW QUESTION 6

- (Exam Topic 1)

A technician is installing a new fiber connection to a network device in a datacenter. The connection from the device to the switch also traverses a patch panel connection. The chain of connections is in the following order:

```
Device
LC/LC patch cable Patch panel
Cross-connect fiber cable Patch panel
LC/LC patch cable Switch
```

The connection is not working. The technician has changed both patch cables with known working patch cables. The device had been tested and was working properly before being installed. Which of the following is the MOST likely cause of the issue?

- A. TX/RX is reversed
- B. An incorrect cable was used
- C. The device failed during installation
- D. Attenuation is occurring

**Answer:** A

**NEW QUESTION 7**

- (Exam Topic 1)

A fiber link connecting two campus networks is broken. Which of the following tools should an engineer use to detect the exact break point of the fiber link?

- A. OTDR
- B. Tone generator
- C. Fusion splicer
- D. Cable tester
- E. PoE injector

**Answer:** A

**NEW QUESTION 8**

- (Exam Topic 1)

A workstation is configured with the following network details:

IP address	Subnet mask	Default gateway
10.1.2.23	10.1.2.0/27	10.1.2.1

Software on the workstation needs to send a query to the local subnet broadcast address. To which of the following addresses should the software be configured to send the query?

- A. 10.1.2.0
- B. 10.1.2.1
- C. 10.1.2.23
- D. 10.1.2.255
- E. 10.1.2.31

**Answer:** E

**NEW QUESTION 9**

- (Exam Topic 1)

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

**Answer:** B

**NEW QUESTION 10**

- (Exam Topic 1)

A user reports being unable to access network resources after making some changes in the office. Which of the following should a network technician do FIRST?

- A. Check the system's IP address
- B. Do a ping test against the servers
- C. Reseat the cables into the back of the PC
- D. Ask what changes were made

**Answer:** D

**NEW QUESTION 10**

- (Exam Topic 1)

A network administrator redesigned the positioning of the APs to create adjacent areas of wireless coverage. After project validation, some users still report poor connectivity when their devices maintain an association to a distanced AP. Which of the following should the network administrator check FIRST?

- A. Validate the roaming settings on the APs and WLAN clients
- B. Verify that the AP antenna type is correct for the new layout
- C. Check to see if MU-MIMO was properly activated on the APs
- D. Deactivate the 2.4GHz band on the APS

**Answer:** A

**NEW QUESTION 13**

- (Exam Topic 1)

A network engineer is investigating reports of poor network performance. Upon reviewing a device configuration, the engineer finds that duplex settings are mismatched on both ends. Which of the following would be the MOST likely result of this finding?

- A. Increased CRC errors
- B. Increased giants and runts
- C. Increased switching loops
- D. Increased device temperature

**Answer:** A

#### NEW QUESTION 17

- (Exam Topic 1)

Which of the following service models would MOST likely be used to replace on-premises servers with a cloud solution?

- A. PaaS
- B. IaaS
- C. SaaS
- D. Disaster recovery as a Service (DRaaS)

**Answer:** B

#### NEW QUESTION 18

- (Exam Topic 1)

A technician is installing a high-density wireless network and wants to use an available frequency that supports the maximum number of channels to reduce interference. Which of the following standard 802.11 frequency ranges should the technician look for while reviewing WAP specifications?

- A. 2.4GHz
- B. 5GHz
- C. 6GHz
- D. 900MHz

**Answer:** B

#### NEW QUESTION 20

- (Exam Topic 1)

A network technician is manually configuring the network settings for a new device and is told the network block is 192.168.0.0/20. Which of the following subnets should the technician use?

- A. 255.255.128.0
- B. 255.255.192.0
- C. 255.255.240.0
- D. 255.255.248.0

**Answer:** C

#### NEW QUESTION 25

- (Exam Topic 1)

A technician wants to deploy a new wireless network that comprises 30 WAPs installed throughout a three-story office building. All the APs will broadcast the same SSID for client access. Which of the following BEST describes this deployment?

- A. Extended service set
- B. Basic service set
- C. Unified service set
- D. Independent basic service set

**Answer:** B

#### NEW QUESTION 27

- (Exam Topic 1)

A network administrator is implementing OSPF on all of a company's network devices. Which of the following will MOST likely replace all the company's hubs?

- A. A Layer 3 switch
- B. A proxy server
- C. A NGFW
- D. A WLAN controller

**Answer:** A

#### NEW QUESTION 32

- (Exam Topic 1)

Which of the following systems would MOST likely be found in a screened subnet?

- A. RADIUS
- B. FTP
- C. SQL
- D. LDAP

**Answer:** B

#### NEW QUESTION 35

- (Exam Topic 1)

A technician is configuring a network switch to be used in a publicly accessible location. Which of the following should the technician configure on the switch to prevent unintended connections?

- A. DHCP snooping
- B. Geofencing
- C. Port security
- D. Secure SNMP

**Answer: C**

#### NEW QUESTION 38

- (Exam Topic 1)

A systems administrator needs to improve WiFi performance in a densely populated office tower and use the latest standard. There is a mix of devices that use 2.4 GHz and 5 GHz. Which of the following should the systems administrator select to meet this requirement?

- A. 802.11ac
- B. 802.11ax
- C. 802.11g
- D. 802.11n

**Answer: B**

#### NEW QUESTION 40

- (Exam Topic 1)

A technician is assisting a user who cannot connect to a network resource. The technician first checks for a link light. According to troubleshooting methodology, this is an example of:

- A. using a bottom-to-top approach.
- B. establishing a plan of action.
- C. documenting a finding.
- D. questioning the obvious.

**Answer: D**

#### NEW QUESTION 42

- (Exam Topic 1)

A new cabling certification is being requested every time a network technician rebuilds one end of a Cat 6 (vendor-certified) cable to create a crossover connection that is used to connect switches. Which of the following would address this issue by allowing the use of the original cable?

- A. CSMA/CD
- B. LACP
- C. PoE+
- D. MDIX

**Answer: D**

#### NEW QUESTION 44

- (Exam Topic 1)

A technician is troubleshooting a network switch that seems to stop responding to requests intermittently whenever the logging level is set for debugging. Which of the following metrics should the technician check to begin troubleshooting the issue?

- A. Audit logs
- B. CPU utilization
- C. CRC errors
- D. Jitter

**Answer: B**

#### NEW QUESTION 45

- (Exam Topic 1)

An IT director is setting up new disaster and HA policies for a company. Limited downtime is critical to operations. To meet corporate requirements, the director set up two different datacenters across the country that will stay current on data and applications. In the event of an outage, the company can immediately switch from one datacenter to another. Which of the following does this BEST describe?

- A. A warm site
- B. Data mirroring
- C. Multipathing
- D. Load balancing
- E. A hot site

**Answer: E**

#### NEW QUESTION 49

- (Exam Topic 1)

Which of the following technologies provides a failover mechanism for the default gateway?

- A. FHRP
- B. LACP
- C. OSPF
- D. STP

**Answer:** A

#### NEW QUESTION 52

- (Exam Topic 1)

A network engineer performs the following tasks to increase server bandwidth:

Connects two network cables from the server to a switch stack

Configure LACP on the switchports

Verifies the correct configurations on the switch interfaces

Which of the following needs to be configured on the server?

- A. Load balancing
- B. Multipathing
- C. NIC teaming
- D. Clustering

**Answer:** C

#### NEW QUESTION 54

- (Exam Topic 1)

A client recently added 100 users who are using VMs. All users have since reported slow or unresponsive desktops. Reports show minimal network congestion, zero packet loss, and acceptable packet delay. Which of the following metrics will MOST accurately show the underlying performance issues? (Choose two.)

- A. CPU usage
- B. Memory
- C. Temperature
- D. Bandwidth
- E. Latency
- F. Jitter

**Answer:** AB

#### NEW QUESTION 57

- (Exam Topic 1)

A network technician needs to ensure outside users are unable to telnet into any of the servers at the datacenter. Which of the following ports should be blocked when checking firewall configuration?

- A. 22
- B. 23
- C. 80
- D. 3389
- E. 8080

**Answer:** B

#### NEW QUESTION 60

- (Exam Topic 1)

A branch of a company recently switched to a new ISP. The network engineer was given a new IP range to assign. The ISP assigned 196.26.4.0/26, and the branch gateway router now has the following configurations on the interface that peers to the ISP:

```
IP address:      196.26.4.30
Subnet mask:     255.255.255.224
Gateway:        196.24.4.1
```

The network engineer observes that all users have lost Internet connectivity. Which of the following describes the issue?

- A. The incorrect subnet mask was configured
- B. The incorrect gateway was configured
- C. The incorrect IP address was configured
- D. The incorrect interface was configured

**Answer:** A

#### NEW QUESTION 65

- (Exam Topic 1)

A technician is searching for a device that is connected to the network and has the device's physical network address. Which of the following should the technician review on the switch to locate the device's network port?

- A. IP route table
- B. VLAN tag
- C. MAC table
- D. QoS tag

**Answer: C**

**NEW QUESTION 67**

- (Exam Topic 2)

There are two managed legacy switches running that cannot be replaced or upgraded. These switches do not support cryptographic functions, but they are password protected. Which of the following should a network administrator configure to BEST prevent unauthorized access?

- A. Enable a management access list
- B. Disable access to unnecessary services.
- C. Configure a stronger password for access
- D. Disable access to remote management
- E. Use an out-of-band access method.

**Answer: A**

**NEW QUESTION 71**

- (Exam Topic 2)

A systems administrator is running a VoIP network and is experiencing jitter and high latency. Which of the following would BEST help the administrator determine the cause of these issues?

- A. Enabling RADIUS on the network
- B. Configuring SNMP traps on the network
- C. Implementing LDAP on the network
- D. Establishing NTP on the network

**Answer: B**

**NEW QUESTION 73**

- (Exam Topic 2)

Which of the following policies should be referenced when a user wants to access work email on a personal cell phone?

- A. Offboarding policy
- B. Acceptable use policy
- C. BYOD policy
- D. Remote access policy

**Answer: C**

**NEW QUESTION 78**

- (Exam Topic 2)

A network technician is observing the behavior of an unmanaged switch when a new device is added to the network and transmits data. Which of the following BEST describes how the switch processes this information?

- A. The data is flooded out of every port
- B. including the one on which it came in.
- C. The data is flooded out of every port but only in the VLAN where it is located.
- D. The data is flooded out of every port, except the one on which it came in
- E. The data is flooded out of every port, excluding the VLAN where it is located

**Answer: C**

**NEW QUESTION 79**

- (Exam Topic 2)

Which of the following security devices would be BEST to use to provide mechanical access control to the MDF/IDF?

- A. A smart card
- B. A key fob
- C. An employee badge
- D. A door lock

**Answer: B**

**NEW QUESTION 82**

- (Exam Topic 2)

At the destination host, which of the following OSI model layers will discard a segment with a bad checksum in the UDP header?

- A. Network
- B. Data link
- C. Transport
- D. Session

**Answer: C**

**NEW QUESTION 83**

- (Exam Topic 2)

A network technician has multimode fiber optic cable available in an existing IDF. Which of the following Ethernet standards should the technician use to connect the network switch to the existing fiber?

- A. 10GBaseT
- B. 1000BaseT
- C. 1000BaseSX
- D. 1000BaseLX

**Answer:** A

**NEW QUESTION 86**

- (Exam Topic 2)

A city has hired a new employee who needs to be able to work when traveling at home and at the municipal sourcing of a neighboring city that snares services. The employee is issued a laptop, and a technician needs to train the employee on the appropriate solutions for secure access to the network from all the possible locations On which of the following solutions would the technician MOST likely train the employee?

- A. Site-to-site VPNs between the two city locations and client-to-site software on the employee's laptop for all other remote access
- B. Client-to-site VPNs between the travel locations and site-to-site software on the employee's laptop for all other remote access
- C. Client-to-site VPNs between the two city locations and site-to-site software on the employee's laptop for all other remote access
- D. Site-to-site VPNs between the home and city locations and site-to-site software on the employee's laptop for all other remote access

**Answer:** A

**NEW QUESTION 91**

- (Exam Topic 2)

A network administrator wants to analyze attacks directed toward the company's network. Which of the following must the network administrator implement to assist in this goal?

- A. A honeypot
- B. Network segmentation
- C. Antivirus
- D. A screened subnet

**Answer:** A

**NEW QUESTION 93**

- (Exam Topic 2)

A company that uses VoIP telephones is experiencing intermittent issues with one-way audio and dropped conversations The manufacturer says the system will work if ping times are less than 50ms. The company has recorded the following ping times:

10ms	10ms	10ms	100ms	70ms	5ms	5ms	80ms	100ms	5ms	5ms
------	------	------	-------	------	-----	-----	------	-------	-----	-----

Which of the following is MOST likely causing the issue?

- A. Attenuation
- B. Latency
- C. VLAN mismatch
- D. Jitter

**Answer:** A

**NEW QUESTION 98**

- (Exam Topic 2)

Which of the following policies is MOST commonly used for guest captive portals?

- A. AUP
- B. DLP
- C. BYOD
- D. NDA

**Answer:** A

**NEW QUESTION 103**

- (Exam Topic 2)

A technician is troubleshooting a previously encountered issue. Which of the following should the technician reference to find what solution was implemented to resolve the issue?

- A. Standard operating procedures
- B. Configuration baseline documents
- C. Work instructions
- D. Change management documentation

**Answer:** A

**NEW QUESTION 104**

- (Exam Topic 2)

A network technician is investigating an issue with a desktop that is not connecting to the network. The desktop was connecting successfully the previous day, and

no changes were made to the environment. The technician locates the switchport where the device is connected and observes the LED status light on the switchport is not lit even though the desktop is turned on. Other devices that are plugged into the switch are connecting to the network successfully. Which of the following is MOST likely the cause of the desktop not connecting?

- A. Transceiver mismatch
- B. VLAN mismatch
- C. Port security
- D. Damaged cable
- E. Duplex mismatch

**Answer: C**

#### NEW QUESTION 105

- (Exam Topic 2)

A user is having difficulty with video conferencing and is looking for assistance. Which of the following would BEST improve performance?

- A. Packet shaping
- B. Quality of service
- C. Port mirroring
- D. Load balancing

**Answer: B**

#### NEW QUESTION 107

- (Exam Topic 2)

A network technician is investigating an IP phone that does not register in the VoIP system. Although it received an IP address, it did not receive the necessary DHCP options. The information that is needed for the registration is distributed by the DHCP scope. All other IP phones are working properly. Which of the following does the technician need to verify?

- A. VLAN mismatch
- B. Transceiver mismatch
- C. Latency
- D. DHCP exhaustion

**Answer: A**

#### NEW QUESTION 112

- (Exam Topic 2)

A user reports a weak signal when walking 20ft (6.1 m) away from the WAP in one direction, but a strong signal when walking 20ft in the opposite direction. The technician has reviewed the configuration and confirmed the channel type is correct. There is no jitter or latency on the connection. Which of the following would be the MOST likely cause of the issue?

- A. Antenna type
- B. Power levels
- C. Frequency
- D. Encryption type

**Answer: A**

#### NEW QUESTION 117

- (Exam Topic 2)

A packet is assigned a value to ensure it does not traverse a network indefinitely. Which of the following BEST represents this value?

- A. Zero Trust
- B. Planned obsolescence
- C. Time to live
- D. Caching

**Answer: C**

#### NEW QUESTION 119

- (Exam Topic 2)

Which of the following VPN configurations should be used to separate Internet and corporate traffic?

- A. Split-tunnel
- B. Remote desktop gateway
- C. Site-to-site
- D. Out-of-band management

**Answer: A**

#### NEW QUESTION 124

- (Exam Topic 2)

A network administrator is required to ensure that auditors have read-only access to the system logs, while systems administrators have read and write access to the system logs, and operators have no access to the system logs. The network administrator has configured security groups for each of these functional categories. Which of the following security capabilities will allow the network administrator to maintain these permissions with the LEAST administrative effort?

- A. Mandatory access control
- B. User-based permissions
- C. Role-based access
- D. Least privilege

**Answer:** C

#### NEW QUESTION 129

- (Exam Topic 2)

An organization wants to implement a method of centrally managing logins to network services. Which of the following protocols should the organization use to allow for authentication, authorization and auditing?

- A. MS-CHAP
- B. RADIUS
- C. LDAPS
- D. RSTP

**Answer:** A

#### NEW QUESTION 132

- (Exam Topic 2)

A business is using the local cable company to provide Internet access. Which of the following types of cabling will the cable company MOST likely use from the demarcation point back to the central office?

- A. Multimode
- B. Cat 5e
- C. RG-6
- D. Cat 6
- E. 100BASE-T

**Answer:** C

#### NEW QUESTION 133

- (Exam Topic 3)

Which of the following is an advanced distance vector routing protocol that automates routing tables and also uses some features of link-state routing protocols?

- A. OSPF
- B. RIP
- C. EIGRP
- D. BGP

**Answer:** C

#### Explanation:

EIGRP is an advanced distance vector routing protocol that is able to automatically update routing tables and also uses features of link-state routing protocols, such as the ability to send updates about the current topology of the network. EIGRP also has the ability to use a variety of algorithms to determine the best route for a packet to take, allowing for more efficient routing across the network.

#### NEW QUESTION 138

- (Exam Topic 3)

A technician removes an old PC from the network and replaces it with a new PC that is unable to connect to the LAN. Which of the following is MOST likely the cause of the issue?

- A. Port security
- B. Port tagging
- C. Port aggregation
- D. Port mirroring

**Answer:** A

#### Explanation:

It is most likely that the issue is caused by port security, as this is a feature that can prevent new devices from connecting to the LAN. Port tagging, port aggregation, and port mirroring are all features that are used to manage traffic on the network, but they are not related to the connectivity of new devices. If the technician has configured port security on the network and the new PC does not meet the security requirements, it will not be able to connect to the LAN.

#### NEW QUESTION 140

- (Exam Topic 3)

Which of the following is most likely to have the HIGHEST latency while being the most accessible?

- A. Satellite
- B. DSL
- C. Cable
- D. 4G

**Answer:** A

#### NEW QUESTION 142

- (Exam Topic 3)

An ISP is providing Internet to a retail store and has terminated its point of connection using a standard Cat 6 pin-out. Which of the following terminations should the technician use when running a cable from the ISP's port to the front desk?

- A. F-type connector
- B. TIA/EIA-568-B
- C. LC
- D. SC

**Answer: B**

**Explanation:**

The termination that the technician should use when running a cable from the ISP's port to the front desk is B. TIA/EIA-568-B. This is a standard pin-out for Cat 6 cables that is used for Ethernet and other network physical layers. It specifies how to arrange the eight wires in an RJ45 connector, which is a common type of connector for network cables.

**NEW QUESTION 145**

- (Exam Topic 3)

Which of the following types of connections would need to be set up to provide access from the internal network to an external network so multiple satellite offices can communicate securely using various ports and protocols?

- A. Client-to-site VPN
- B. Clientless VPN
- C. RDP
- D. Site-to-site VPN
- E. SSH

**Answer: D**

**NEW QUESTION 146**

- (Exam Topic 3)

Which of the following architectures reduces network latency by enforcing a limit on the number of switching devices on the frame's path between any internal hosts?

- A. Spine and leaf
- B. Software-defined network
- C. Three-tiered
- D. Collapsed core

**Answer: A**

**Explanation:**

It does this by using a two-level hierarchy of switches, where the spine switches connect to the leaf switches, which in turn connect to the end hosts. This reduces the number of hops a packet must take from one host to another, thus reducing latency. According to the CompTIA Network+ N10-008 Exam Guide, the Spine and Leaf topology is a modern architecture that is used to reduce latency in large networks.

**NEW QUESTION 148**

- (Exam Topic 3)

Which of the following BEST describes a North-South traffic flow?

- A. A public Internet user accessing a published web server
- B. A database server communicating with another clustered database server
- C. A Layer 3 switch advertising routes to a router
- D. A management application connecting to managed devices

**Answer: D**

**NEW QUESTION 152**

- (Exam Topic 3)

Which of the following topologies requires the MOST connections when designing a network?

- A. Mesh
- B. Star
- C. Bus
- D. Ring

**Answer: A**

**NEW QUESTION 157**

- (Exam Topic 3)

A medical building offers patients Wi-Fi in the waiting room. Which of the following security features would be the BEST solution to provide secure connections and keep the medical data protected?

- A. Isolating the guest network
- B. Securing SNMP
- C. MAC filtering
- D. Disabling unneeded switchports

**Answer:** A

**NEW QUESTION 162**

- (Exam Topic 3)

Which of the following is a valid and cost-effective solution to connect a fiber cable into a network switch without available SFP ports?

- A. Use a media converter and a UTP cable
- B. Install an additional transceiver module and use GBICs
- C. Change the type of connector from SC to F-type
- D. Use a loopback adapter to make the connection

**Answer:** A

**NEW QUESTION 164**

- (Exam Topic 3)

A network technician needs to install security updates on several switches on the company's network. The management team wants this completed as quickly and efficiently as possible. Which of the following should the technician do to perform the updates?

- A. Upload the security update onto each switch using a terminal emulator and a console cable.
- B. Configure a TFTP server
- C. SSH into each device, and perform the update.
- D. Replace each old switch with new switches that have the updates already performed.
- E. Connect a USB memory stick to each switch and perform the update.

**Answer:** B

**NEW QUESTION 168**

- (Exam Topic 3)

During a recent security audit, a contracted penetration tester discovered the organization uses a number of insecure protocols. Which of the following ports should be disallowed so only encrypted protocols are allowed? (Select TWO).

- A. 22
- B. 23
- C. 69
- D. 443
- E. 587
- F. 8080

**Answer:** BC

**NEW QUESTION 169**

- (Exam Topic 3)

An administrator would like to allow Windows clients from outside the office to access workstations without using third-party software. Which of the following access methods would meet this requirement?

- A. Remote desktop gateway
- B. Split tunnel
- C. Site-to-site VPN
- D. VNC

**Answer:** A

**Explanation:**

To allow Windows clients from outside the office to access workstations without using third-party software, the administrator can use the Remote Desktop Protocol (RDP). RDP is a built-in feature of the Windows operating system that allows users to remotely connect to and control other Windows computers over a network connection.

To use RDP, the administrator will need to enable the Remote Desktop feature on the workstations that need to be accessed, and ensure that the appropriate firewall rules are in place to allow RDP traffic to pass through. The administrator will also need to provide the remote users with the necessary credentials to access the workstations.

Once RDP is set up and configured, the remote users can use the Remote Desktop client on their own computers to connect to the workstations and access them as if they were physically present in the office. This allows the administrator to provide remote access to the workstations without the need for any additional software or third-party tools.

**NEW QUESTION 171**

- (Exam Topic 3)

An international company is transferring its IT assets including a number of WAPs from the United States to an office in Europe for deployment. Which of the following considerations should the company research before implementing the wireless hardware?

- A. WPA2 cipher
- B. Regulatory impacts
- C. CDMA configuration
- D. 802.11 standards

**Answer:** B

**Explanation:**

When transferring IT assets, including wireless access points (WAPs), from one country to another, it's important to research the regulatory impacts of the move. Different countries have different regulations and compliance requirements for wireless devices, such as frequency bands, power levels, and encryption standards.

Failing to comply with these regulations can result in fines or other penalties.

**NEW QUESTION 176**

- (Exam Topic 3)

Which of the following topologies is designed to fully support applications hosted in on-premises data centers, public or private clouds, and SaaS services?

- A. SDWAN
- B. MAN
- C. PAN
- D. MPLS

**Answer:** A

**NEW QUESTION 177**

- (Exam Topic 3)

A company streams video to multiple devices across a campus. When this happens, several users report a degradation of network performance. Which of the following would MOST likely address this issue?

- A. Enable IGMP snooping on the switches.
- B. Implement another DHCP server.
- C. Reconfigure port tagging for the video traffic.
- D. Change the SSID of the APs

**Answer:** A

**NEW QUESTION 178**

- (Exam Topic 3)

Which of the following needs to be tested to achieve a Cat 6a certification for a company's data cabling?

- A. RJ11
- B. LC ports
- C. Patch panel
- D. F-type connector

**Answer:** D

**NEW QUESTION 182**

- (Exam Topic 3)

A technician performed a manual reconfiguration of a firewall, and network connectivity was reestablished. Some connection events that were previously sent to a syslog server are no longer being generated by the firewall. Which of the following should the technician perform to fix the issue?

- A. Adjust the proper logging level on the new firewall.
- B. Tune the filter for logging the severity level on the syslog server.
- C. Activate NetFlow traffic between the syslog server and the firewall
- D. Restart the SNMP service running on the syslog server.

**Answer:** D

**NEW QUESTION 187**

- (Exam Topic 3)

A company cell phone was stolen from a technician's vehicle. The cell phone has a passcode, but it contains sensitive information about clients and vendors. Which of the following should also be enabled?

- A. Factory reset
- B. Autolock
- C. Encryption
- D. Two-factor authentication

**Answer:** C

**NEW QUESTION 191**

- (Exam Topic 3)

A Wi-Fi network was originally configured to be able to handle interference from a microwave oven. The microwave oven was recently removed from the office. Now the network administrator wants to optimize the system to maximize the range of the signal. The main sources of signal degradation are the numerous cubicles and wooden walls between the WAP and the intended destination. Which of the following actions should the administrator take?

- A. Implement CDMA.
- B. Change from omni to directional.
- C. Change the SSID.
- D. Change the frequency.

**Answer:** D

**Explanation:**

- the microwave was already removed from the office
- the signal is OK now
- Notice that the question mentions "numerous cubicles and wooden walls" - meaning the signal now won't have the interference as before

- KEY POINT: the admin wants to "maximize the range of the signal:"

Manually change the frequency to 2.4 GHz for more reliable speeds and range. While 5 GHz gives you a stronger signal, it doesn't travel through walls or ceilings as well, so it doesn't give you the best range.

"Microwave ovens: Older microwave ovens, which might not have sufficient shielding, can emit relatively high-powered signals in the 2.4GHz band, resulting in significant interference with WLAN devices operating in the 2.4GHz band."

#### NEW QUESTION 195

- (Exam Topic 3)

An administrator needs to connect two laptops directly to each other using 802.11ac but does not have an AP available. Which of the following describes this configuration?

- A. Basic service set
- B. Extended service set
- C. Independent basic service set
- D. MU-MIMO

**Answer: C**

#### NEW QUESTION 197

- (Exam Topic 3)

Which of the following would MOST likely utilize PoE?

- A. A camera
- B. A printer
- C. A hub
- D. A modem

**Answer: A**

#### Explanation:

A camera is most likely to utilize PoE (Power over Ethernet). PoE is a technology that allows electrical power to be delivered over Ethernet cables. It is used to power a variety of devices, such as cameras, phones, access points, and other networking equipment. Cameras are particularly well-suited for PoE because they are often installed in locations where it is difficult or impossible to run electrical power. By using PoE, cameras can be powered directly over the Ethernet cable, eliminating the need for separate power cables and outlets. Other devices, such as printers, hubs, and modems, are less likely to utilize PoE because they typically do not need to be powered over Ethernet. These devices are usually powered by AC (alternating current) power and are typically connected to a power outlet rather than an Ethernet cable.

#### NEW QUESTION 200

- (Exam Topic 3)

An administrator would like to have two servers at different geographical locations provide fault tolerance and high performance while appearing as one URL to users. Which of the following should the administrator implement?

- A. Load balancing
- B. Multipathing
- C. NIC teaming
- D. Warm site

**Answer: A**

#### Explanation:

Load balancing is a technique that can be used to provide fault tolerance and high performance while appearing as one URL to users. It is achieved by distributing the workload across multiple servers, which are usually located in different geographical locations. This allows for high performance and fault tolerance, as if one server fails, the other will take its place. Additionally, the multiple servers appear as one URL to the users, eliminating the need for the users to switch between servers.

#### NEW QUESTION 202

- (Exam Topic 3)

After HVAC failures caused network outages, the support team decides to monitor the temperatures of all the devices. The network administrator cannot find a command that will display this information. Which of the following will retrieve the necessary information?

- A. SNMP OID values
- B. NetFlow data export
- C. Network baseline configurations
- D. Security information and event management

**Answer: A**

#### Explanation:

The network administrator can use the Simple Network Management Protocol (SNMP) to monitor the temperatures of all the devices. SNMP is a widely-used protocol for managing and monitoring network devices, such as routers, switches, servers, and other networking equipment. SNMP allows network administrators to gather information about the performance and status of devices on the network, including temperature readings.

To retrieve the temperature information, the administrator will have to configure SNMP on the devices and configure SNMP manager software on their computer. Once the SNMP manager software is configured, it will be able to send SNMP requests to the devices and retrieve information such as temperature, voltage, fan speeds, etc. Many network devices have built-in SNMP support, and the administrator may also need to install SNMP agent software on the devices to enable SNMP monitoring.

The administrator can also use some specific command or tool like IPMI (Intelligent Platform Management Interface) or DCIM (Data Center Infrastructure Management) tools for monitoring the temperatures of all the devices.

#### NEW QUESTION 205

- (Exam Topic 3)

Network users reported that a recent firmware upgrade to a firewall did not resolve the issue that prompted the upgrade. Which of the following should be performed NEXT?

- A. Reopen the service ticket, request a new maintenance window, and roll back to the anterior firmware version.
- B. Gather additional information to ensure users' concerns are not been caused by a different issue with similar symptoms.
- C. Employ a divide-and-conquer troubleshooting methodology by engaging the firewall vendor's support.
- D. Escalate the issue to the IT management team in order to negotiate a new SLA with the user's manager.

**Answer:** A

#### NEW QUESTION 207

- (Exam Topic 3)

A systems operator is granted access to a monitoring application, configuration application, and timekeeping application. The operator is denied access to the financial and project management applications by the system's security configuration. Which of the following BEST describes the security principle in use?

- A. Network access control
- B. Least privilege
- C. Multifactor authentication
- D. Separation of duties

**Answer:** D

#### NEW QUESTION 210

- (Exam Topic 3)

Which of the following ports should be used to securely receive mail that is synchronized across multiple devices?

- A. 25
- B. 110
- C. 443
- D. 993

**Answer:** D

#### NEW QUESTION 214

- (Exam Topic 3)

Which of the following allows for an devices within a network to share a highly reliable time source?

- A. NTP
- B. SNMP
- C. SIP
- D. DNS

**Answer:** A

#### Explanation:

Network Time Protocol (NTP) is a protocol used to maintain a highly accurate and reliable clock time on all devices within a network. NTP works by synchronizing the time of all the devices within a network to a single, highly accurate time source. This allows for the time of all the devices to be kept in sync with each other, ensuring a consistent and reliable time source for all devices within the network.

#### NEW QUESTION 218

- (Exam Topic 3)

A technician is checking network devices to look for opportunities to improve security Which of the following toots would BEST accomplish this task?

- A. Wi-Fi analyzer
- B. Protocol analyzer
- C. Nmap
- D. IP scanner

**Answer:** B

#### Explanation:

A protocol analyzer is a tool that can capture and analyze network traffic and identify security issues such as unauthorized devices, malicious packets, or misconfigured settings.

A Wi-Fi analyzer is a tool that can measure the signal strength, interference, and channel usage of wireless networks, but it cannot provide detailed information about network security.

Nmap and IP scanner are tools that can scan network hosts and ports for open services, vulnerabilities, or operating systems, but they cannot monitor network traffic in real time.

#### NEW QUESTION 223

- (Exam Topic 3)

A computer engineer needs to ensure that only a specific workstation can connect to port 1 on a switch. Which of the following features should the engineer configure on the switch interface?

- A. Port tagging
- B. Port security
- C. Port mirroring

D. Port aggregation

**Answer:** B

**Explanation:**

Port security is a feature that can be configured on a switch interface to limit and identify the MAC addresses of workstations that are allowed to connect to that specific port. This can help ensure that only a specific workstation (or workstations) can connect to the interface. According to the CompTIA Network+ Study Manual, "Port security can be used to specify which MAC addresses are allowed to connect to a particular switch port. If a port security violation is detected, the switch can take a number of different actions, such as shutting down the port, sending an SNMP trap, or sending an email alert."

**NEW QUESTION 227**

- (Exam Topic 3)

A company wants to invest in new hardware for the core network infrastructure. The management team requires that the infrastructure be capable of being repaired in less than 60 minutes if any major part fails. Which of the following metrics is MOST likely associated with this requirement?

- A. RPO
- B. MTTR
- C. FHRP
- D. MTBF

**Answer:** B

**Explanation:**

MTTR is directly related to how quickly a system can be repaired if any major part fails. The management team requires that the infrastructure be capable of being repaired in less than 60 minutes, which means they have a low MTTR requirement. MTTR stands for Mean Time To Repair and is a metric used to measure the average amount of time it takes to repair a failed component or system. In this case, the requirement is for the infrastructure to be capable of being repaired in less than 60 minutes if any major part fails, which means the MTTR should be less than 60 minutes.

**NEW QUESTION 230**

- (Exam Topic 3)

A network technician receives a report from the server team that a server's network connection is not working correctly. The server team confirms the server is operating correctly except for the network connection. The technician checks the switchport connected to the server and reviews the following data;

Metric	Value
Bytes input	441,164,698
Bytes output	2,625,115,257
Runts	0
CRCs	5,489
Collisions	1
MDIX	On
Speed	1,000
Duplex	Full

Which of the following should the network technician perform to correct the issue?

- A. Replace the Cat 5 patch cable with a Cat 6 cable
- B. Install a crossover cable between the server and the switch
- C. Reset the switchport configuration.
- D. Use NetFlow data from the switch to isolate the issue.
- E. Disable MDIX on the switchport and reboot the server.

**Answer:** A

**Explanation:**

"Bad cables, incorrect pinouts, or bent pins: Faulty cables (with electrical characteristics preventing successful transmission) or faulty connectors (which do not properly make connections) can prevent successful data transmission at Layer 1. A bad cable could simply be an incorrect category of cable being used for a specific purpose. For example, using a Cat 5 cable (instead of a Cat 6 or higher cable) to connect two 1000BASE-TX devices would result in data corruption. Bent pins in a connector or incorrect pinouts could also cause data to become corrupted."

**NEW QUESTION 235**

- (Exam Topic 3)

Which of the following describes when an active exploit is used to gain access to a network?

- A. Penetration testing
- B. Vulnerability testing
- C. Risk assessment
- D. Posture assessment
- E. Baseline testing

**Answer:** A

**Explanation:**

Penetration testing is a type of security testing that is used to assess the security of a system or network by actively exploiting known vulnerabilities. It is used to simulate an attack on the system and identify any weaknesses that may be exploited by malicious actors. As stated in the CompTIA Security+ Study Guide, "penetration testing is a type of security assessment that attempts to gain unauthorized access to networks and systems by exploiting security vulnerabilities."

**NEW QUESTION 238**

- (Exam Topic 3)

A user calls the help desk to report being unable to reach a file server. The technician logs in to the user's computer and verifies that pings fail to respond back when trying to reach the file server. Which of the following would BEST help the technician verify whether the file server is reachable?

- A. netstat
- B. ipconfig
- C. nslookup
- D. traceroute

**Answer: D**

**Explanation:**

Traceroute is a network diagnostic tool that allows you to trace the path that network packets take from one device to another. By running traceroute to the file server, the technician can see the sequence of devices and networks that the packets pass through on their way to the file server. This can help the technician to determine if there is a problem with the network connection between the user's computer and the file server, or if the issue is with the file server itself.

**NEW QUESTION 241**

- (Exam Topic 3)

An IT technician successfully connects to the corporate wireless network at a bank. While performing some tests, the technician observes that the physical address of the DHCP server has changed even though the network connection has not been lost. Which of the following would BEST explain this change?

- A. Server upgrade
- B. Duplicate IP address
- C. Scope exhaustion
- D. Rogue server

**Answer: D**

**Explanation:**

A rogue server is a DHCP server on a network that is not under the administrative control of the network staff 1. It may provide incorrect IP addresses or other network configuration information to devices on the network, causing them to lose connectivity or be vulnerable to attacks2. The physical address of the DHCP server may change if a rogue server takes over the role of assigning IP addresses to devices on the network. This can be detected by monitoring DHCP traffic or using tools such as RogueChecker2.

**NEW QUESTION 243**

- (Exam Topic 3)

A network administrator is investigating a network event that is causing all communication to stop. The network administrator is unable to use SSH to connect to the switch but is able to gain access using the serial console port. While monitoring port statistics, the administrator sees the following:

Total Rx (bps)	23,041,464	Total Tx (bps)	621,032
Unicast Rx (Pkts/sec)	102,465	Unicast Tx (Pkts/sec)	66
B/Mcast Rx (Pkts/sec)	21,456.465	B/Mcast Tx (Pkts/sec)	7
Utilization Rx	2.3%	Utilization Tx	0.06%

Which of the following is MOST likely causing the network outage?

- A. Duplicate IP address
- B. High collisions
- C. Asynchronous route
- D. Switch loop

**Answer: B**

**NEW QUESTION 246**

- (Exam Topic 3)

Which of the following uses the link-state routing algorithm and operates within a single autonomous system?

- A. EIGRP
- B. OSPF
- C. RIP
- D. BGP

**Answer: B**

**Explanation:**

OSPF uses a link state routing algorithm and falls into the group of interior routing protocols, operating within a single autonomous system (AS). OSPF is perhaps the most widely used interior gateway protocol (IGP) in large enterprise networks

**NEW QUESTION 249**

- (Exam Topic 3)

A company joins a bank's financial network and establishes a connection to the clearinghouse servers in the range 192.168.124.0/27. An IT technician then realizes the range exists within the VM pool at the data center. Which of the following is the BEST way for the technician to connect to the bank's servers?

- A. NAT
- B. PAT
- C. CIDR
- D. SLAAC

**Answer:** A

#### NEW QUESTION 250

- (Exam Topic 3)

Due to space constraints in an IDF, a network administrator can only do a single switch to accommodate three data networks. The administrator needs a configuration that will allow each device to access its expected network without additional connections. The configuration must also allow each device to access the rest of the network. Which of the following should the administrator do to meet these requirements? (Select TWO).

- A. Untag the three VLANs across the uplink
- B. Tag an individual VLAN across the uplink
- C. Untag an individual VLAN per device port
- D. Tag an individual VLAN per device port
- E. Tag the three VLANs across the uplink.
- F. Tag the three VLANs per device port.

**Answer:** AC

#### Explanation:

To achieve this, you should do two things:

- Tag the three VLANs across the uplink port that connects to another switch or router. This will allow data packets from different VLANs to cross over into other networks.
- Untag an individual VLAN per device port that connects to an end device. This will assign each device to its expected network without additional connections.

#### NEW QUESTION 251

- (Exam Topic 3)

To access production applications and data, developers must first connect remotely to a different server. From there, the developers are able to access production data. Which of the following does this BEST represent?

- A. A management plane
- B. A proxy server
- C. An out-of-band management device
- D. A site-to-site VPN
- E. A jump box

**Answer:** E

#### NEW QUESTION 253

- (Exam Topic 3)

ARP spoofing would normally be a part of:

- A. an on-path attack.
- B. DNS poisoning.
- C. a DoS attack.
- D. a rogue access point.

**Answer:** A

#### NEW QUESTION 257

- (Exam Topic 3)

A technician is connecting a Cat 6 Ethernet cable to a device that only has LC ports. Which of the following will the technician MOST likely use to accomplish this task?

- A. A bridge
- B. A media converter
- C. A repeater
- D. A router

**Answer:** B

#### NEW QUESTION 258

- (Exam Topic 3)

A network technician is having issues connecting an IoT sensor to the internet. The WLAN settings were enabled via a custom command line, and a proper IP address assignment was received on the wireless interface. However, when trying to connect to the internet, only HTTP redirections are being received when data is requested. Which of the following will point to the root cause of the issue?

- A. Verifying if an encryption protocol mismatch exists.
- B. Verifying if a captive portal is active for the WLAN.
- C. Verifying the minimum RSSI for operation in the device's documentation
- D. Verifying EIRP power settings on the access point.

**Answer:** C

**Explanation:**

A captive portal is a web page that is displayed to a user before they can access the internet or other network resources. This is often used in public or guest networks to present users with a login or terms and conditions page before they can access the internet. If a captive portal is active on the WLAN, it would explain why the IoT sensor is only receiving HTTP redirections when trying to connect to the internet.

**NEW QUESTION 263**

- (Exam Topic 3)

Which of the following topologies requires the MOST connections when designing a network?

- A. Mesh
- B. Star
- C. Bus
- D. Ring

**Answer:** A

**NEW QUESTION 266**

- (Exam Topic 3)

Which of the following types of datacenter architectures will MOST likely be used in a large SDN and can be extended beyond the datacenter? (Choose two.)

- A. iSCSI
- B. FCoE
- C. Three-tiered network
- D. Spine and leaf
- E. Top-of-rack switching

**Answer:** CD

**NEW QUESTION 270**

- (Exam Topic 3)

A company needs to virtualize a replica of its internal physical network without changing the logical topology and the way that devices behave and are managed. Which of the following technologies meets this requirement?

- A. NFV
- B. SDWAN
- C. VIP
- D. MPLS

**Answer:** A

**Explanation:**

Network Function Virtualization (NFV) is a technology that allows for the virtualization of a replica of a network's physical topology and the way it behaves without changing the logical topology and the way that devices are managed. NFV allows for the virtualization of network functions such as routers, firewalls, and switches, resulting in increased flexibility and scalability. This makes NFV an ideal technology for companies looking to virtualize a replica of their internal physical network.

**NEW QUESTION 275**

- (Exam Topic 3)

Which of the following describes the ability of a corporate IT department to expand its cloud-hosted VM environment with minimal effort?

- A. Scalability
- B. Load balancing
- C. Multitenancy
- D. Geo-redundancy

**Answer:** A

**Explanation:**

Scalability is the ability of a corporate IT department to expand its cloud-hosted virtual machine (VM) environment with minimal effort. This allows IT departments to quickly and easily scale up their cloud environment to meet increased demand. Scalability also allows for the efficient use of resources, as IT departments can quickly and easily scale up or down as needed.

**NEW QUESTION 280**

- (Exam Topic 3)

Which of the following is the primary function of the core layer of the three-tiered model?

- A. Routing
- B. Repeating
- C. Bridging
- D. Switching

**Answer:** A

**Explanation:**

<https://www.omniseu.com/cisco-certified-network-associate-ccna/three-tier-hierarchical-network-model.php>

Core Layer consists of biggest, fastest, and most expensive routers with the highest model numbers and Core Layer is considered as the back bone of networks.

Core Layer routers are used to merge geographically separated networks. The Core Layer routers move information on the network as fast as possible. The switches operating at core layer switches packets as fast as possible.

**NEW QUESTION 285**

- (Exam Topic 3)

A corporate client is experiencing global system outages. The IT team has identified multiple potential underlying causes throughout the enterprise. Each team member has been assigned an area to trouble shoot. Which of the following approaches is being used?

- A. Divide-and-conquer
- B. Top-to-bottom
- C. Bottom-to-top
- D. Determine if anything changed

**Answer: A**

**NEW QUESTION 287**

- (Exam Topic 3)

A network engineer receives the following when connecting to a switch to configure a port:

```
telnet 10.1.200.1
Connecting to 10.1.200.1...Could not open connection to the host, on port 23: Connect failed.
```

Which of the following is the MOST likely cause for the failure?

- A. The network engineer is using the wrong protocol
- B. The network engineer does not have permission to configure the device
- C. SNMP has been secured with an ACL
- D. The switchport the engineer is trying to configure is down

**Answer: D**

**NEW QUESTION 289**

- (Exam Topic 3)

A network administrator is troubleshooting the communication between two Layer 2 switches that are reporting a very high runt count. After trying multiple ports on both switches, the issue persists. Which of the following should the network administrator perform to resolve the issue?

- A. Increase the MTU size on both switches.
- B. Recertify the cable between both switches.
- C. Perform a factory reset on both switches.
- D. Enable debug logging on both switches.

**Answer: A**

**NEW QUESTION 294**

- (Exam Topic 3)

A network administrator is trying to identify a device that is having issues connecting to a switchport. Which of the following would BEST help identify the issue?

- A. A syslog server
- B. Change management records
- C. A rack diagram
- D. The security log

**Answer: A**

**NEW QUESTION 297**

- (Exam Topic 3)

Users within a corporate network need to connect to the Internet, but corporate network policy does not allow direct connections. Which of the following is MOST likely to be used?

- A. Proxy server
- B. VPN client
- C. Bridge
- D. VLAN

**Answer: A**

**NEW QUESTION 299**

- (Exam Topic 3)

A new student is given credentials to log on to the campus Wi-Fi. The student stores the password in a laptop and is able to connect; however, the student is not able to connect with a phone when only a short distance from the laptop. Given the following information:

Signal strength	90%
Coverage	80%
Interference	15%
Number of connection attempts	10

Which of the following is MOST likely causing this connection failure?

- A. Transmission speed
- B. Incorrect passphrase
- C. Channel overlap
- D. Antenna cable attenuation/signal loss

**Answer:** B

#### NEW QUESTION 300

- (Exam Topic 3)

A help desk technician is concerned that a client's network cable issues may be causing intermittent connectivity. Which of the following would help the technician determine if this is the issue?

- A. Run the show interface command on the switch
- B. Run the traceroute command on the server
- C. Run iperf on the technician's desktop
- D. Ping the client's computer from the router
- E. Run a port scanner on the client's IP address

**Answer:** A

#### Explanation:

To determine if a client's network cable issues may be causing intermittent connectivity, the help desk technician can run the show interface command on the switch. This command allows the technician to view the status and statistics of the various interfaces on the switch, including the physical link status and the number of transmitted and received packets. If the interface is experiencing a large number of errors or dropped packets, this could indicate a problem with the network cable or with the connection between the client's device and the switch.

"Cisco routers and switches have a show interfaces IOS command that provides interface statistics/status information, including link state (up/down), speed/duplex, send/receive traffic, cyclic redundancy checks (CRCs), and protocol packet and byte counts."

#### NEW QUESTION 302

- (Exam Topic 3)

Which of the following would be the BEST choice to connect branch sites to a main office securely?

- A. VPN headend
- B. Proxy server
- C. Bridge
- D. Load balancer

**Answer:** A

#### Explanation:

Host-to-Site, or Client-to-Site, VPN allows for remote servers, clients, and other hosts to establish tunnels through a VPN gateway (or VPN headend) via a private network. The tunnel between the headend and the client host encapsulates and encrypts data.

#### NEW QUESTION 305

- (Exam Topic 3)

A company is moving to a new building designed with a guest waiting area that has existing network ports. Which of the following practices would BEST secure the network?

- A. Ensure all guests sign an NDA.
- B. Disable unneeded switchports in the area.
- C. Lower the radio strength to reduce Wi-Fi coverage in the waiting area.
- D. Enable MAC filtering to block unknown hardware addresses.

**Answer:** B

#### Explanation:

One of the best practices to secure the network would be to disable unneeded switchports in the guest waiting area. This will prevent unauthorized users from connecting to the network through these ports. It's important to identify which switchports are not in use and disable them, as this will prevent unauthorized access to the network.

Other practices such as ensuring all guests sign an NDA, lowering the radio strength to reduce Wi-Fi coverage in the waiting area and enabling MAC filtering to block unknown hardware addresses are not as effective in securing the network as disabling unneeded switchports. Enforcing an NDA with guests may not stop a malicious user from attempting to access the network, reducing the radio strength only limits the Wi-Fi coverage, and MAC filtering can be easily bypassed by hackers.

#### NEW QUESTION 306

- (Exam Topic 3)

A security administrator is trying to prevent incorrect IP addresses from being assigned to clients on the network. Which of the following would MOST likely prevent this and allow the network to continue to operate?

- A. Configuring DHCP snooping on the switch
- B. Preventing broadcast messages leaving the client network
- C. Blocking ports 67/68 on the client network
- D. Enabling port security on access ports

**Answer:** A

#### Explanation:

To prevent incorrect IP addresses from being assigned to clients on the network and allow the network to continue to operate, the security administrator should consider configuring DHCP (Dynamic Host

Configuration Protocol) snooping on the switch. DHCP snooping is a security feature that is used to prevent unauthorized DHCP servers from operating on a network. It works by allowing the switch to monitor and validate DHCP traffic on the network, ensuring that only legitimate DHCP messages are forwarded to clients. This can help to prevent incorrect IP addresses from being assigned to clients, as it ensures that only authorized DHCP servers are able to provide IP addresses to clients on the network.

#### NEW QUESTION 311

- (Exam Topic 3)

The following DHCP scope was configured for a new VLAN dedicated to a large deployment of 325 IoT sensors:

```
DHCP network scope: 10.10.0.0/24
Exclusion range:    10.10.10.1-10.10.10.10
Gateway:           10.10.0.1
DNS:               10.10.0.2
DHCP option 66 (TFTP): 10.10.10.4
DHCP option 4 (NTP): 10.10.10.5
```

The first 244 IoT sensors were able to connect to the TFTP server, download the configuration file, and register to an IoT management system. The other sensors are being shown as offline. Which of the following should be performed to determine the MOST likely cause of the partial deployment of the sensors?

- A. Check the gateway connectivity to the TFTP server.
- B. Check the DHCP network scope.
- C. Check whether the NTP server is online.
- D. Check the IoT devices for a hardware failure.

**Answer: B**

#### NEW QUESTION 315

- (Exam Topic 3)

A network administrator wants to check all network connections and see the output in integer form. Which of the following commands should the administrator run on the command line?

- A. netstat
- B. netstat -a
- C. netstat -e
- D. netstat -n

**Answer: A**

#### NEW QUESTION 317

- (Exam Topic 3)

Which of the following is conducted frequently to maintain an updated list of a system's weaknesses?

- A. Penetration test
- B. Posture assessment
- C. Risk assessment
- D. Vulnerability scan

**Answer: D**

#### NEW QUESTION 322

- (Exam Topic 3)

A network client is trying to connect to the wrong TCP port. Which of the following responses would the client MOST likely receive?

- A. RST
- B. FIN
- C. ICMP Time Exceeded
- D. Redirect

**Answer: A**

#### NEW QUESTION 325

- (Exam Topic 3)

Which of the following security controls indicates unauthorized hardware modifications?

- A. Biometric authentication
- B. Media device sanitization
- C. Change management policy
- D. Tamper-evident seals

**Answer: A**

#### NEW QUESTION 330

- (Exam Topic 3)

A network administrator is troubleshooting a connectivity performance issue. As part of the troubleshooting process, the administrator performs a traceout from the client to the server, and also from the server to the client. While comparing the outputs, the administrator notes they show different hops between the hosts. Which of the following BEST explains these findings?

- A. Asymmetric routing
- B. A routing loop
- C. A switch loop
- D. An incorrect gateway

**Answer:** C

#### NEW QUESTION 331

- (Exam Topic 3)

A technician notices that equipment is being moved around and misplaced in the server room, even though the room has locked doors and cabinets. Which of the following would be the BEST solution to identify who is responsible?

- A. Install motion detection
- B. Install cameras.
- C. Install tamper detection.
- D. Hire a security guard.

**Answer:** B

#### Explanation:

Installing cameras in the server room is the best solution to identify who is responsible for the equipment being moved and misplaced. Cameras provide a way to monitor the server room in real time and can be used to identify suspicious activity. Additionally, they provide a way to review past activity and allow you to review footage to determine who may be responsible for the misplacement of equipment.

#### NEW QUESTION 332

- (Exam Topic 3)

Which of the following attack vectors represents a large number of devices sending access requests to a website, making it unavailable to respond?

- A. Virus
- B. Botnet
- C. ARP spoofing
- D. DDoS

**Answer:** D

#### NEW QUESTION 333

- (Exam Topic 3)

A technician manages a DHCP scope but needs to allocate a portion of the scope's subnet for statically assigned devices. Which of the following DHCP concepts would be BEST to use to prevent IP address conflicts?

- A. Dynamic assignment
- B. Exclusion range
- C. Address reservation
- D. IP helper

**Answer:** B

#### Explanation:

To prevent IP address conflicts when allocating a portion of a DHCP scope's subnet for statically assigned devices, it is recommended to use the concept of DHCP exclusion ranges. DHCP exclusion ranges allow a DHCP administrator to specify a range of IP addresses within the scope that should not be assigned to DHCP clients. This can be useful in situations where some devices on the network need to be assigned static IP addresses, as it ensures that the statically assigned addresses do not overlap with addresses assigned by the DHCP server. To set up a DHCP exclusion range, the administrator needs to specify the start and end IP addresses of the range, as well as the subnet mask. The DHCP server will then exclude the specified range of addresses from its pool of available addresses, and will not assign them to DHCP clients. By using DHCP exclusion ranges, the technician can ensure that the statically assigned addresses do not conflict with addresses assigned by the DHCP server, and can prevent IP address conflicts on the network.

Anthony Sequeira

"Another frequent configuration you might make in a DHCP implementation is to configure an exclusion range. This is a portion of the address pool that you never want leased out to clients in the network. Perhaps you have numbered your servers 192.168.1.1–192.168.1.10. Because the servers are statically configured with these addresses, you exclude these addresses from the 192.168.1.0/24 pool of addresses."

Mike Meyers

"Exclusion ranges represent an IP address or range of IP addresses from the pool of addresses that are not to be given out by the DHCP server. Exclusions should be made for the static addresses manually configured on servers and router interfaces, so these IP addresses won't be offered to DHCP clients."

#### NEW QUESTION 336

- (Exam Topic 3)

An attacker targeting a large company was able to inject malicious A records into internal name resolution servers. Which of the following attack types was MOST likely used?

- A. DNS poisoning
- B. On-path
- C. IP spoofing
- D. Rogue DHCP

**Answer:** A

#### NEW QUESTION 341

- (Exam Topic 3)

Due to concerns around single points of failure, a company decided to add an additional WAN to the network. The company added a second MPLS vendor to the

current MPLS WAN and deployed an additional WAN router at each site. Both MPLS providers use OSPF on the WAN network, and EIGRP is run internally. The first site to go live with the new WAN is successful, but when the second site is activated significant network issues occur. Which of the following is the MOST likely cause for the WAN instability?

- A. A routing loop
- B. Asymmetrical routing
- C. A switching loop
- D. An incorrect IP address

**Answer: B**

**Explanation:**

Asymmetrical routing is the most likely cause for the WAN instability. When two different routing protocols are used, like OSPF and EIGRP, it can cause asymmetrical routing, which results in traffic being routed differently in each direction. This can lead to instability in the WAN. A CDP neighbor change, a switching loop, or an incorrect IP address are not likely causes for WAN instability.

**NEW QUESTION 345**

- (Exam Topic 3)

A network administrator installed a new data and VoIP network. Users are now experiencing poor call quality when making calls. Which of the following should the administrator do to increase VoIP performance?

- A. Configure a voice VLAN.
- B. Configure LACP on all VoIP phones.
- C. Configure PoE on the network.
- D. Configure jumbo frames on the network.

**Answer: A**

**Explanation:**

"Benefits of Voice VLAN

It ensures that your VoIP (Voice over Internet Phone) devices do not have to contend directly with all the broadcasts and other traffic from the data VLAN. A voice VLAN can simplify network configuration in some circumstances."

<https://community.fs.com/blog/auto-voip-vs-voice-vlan-what-s-the-difference.html> Jumbo Frames

"When jumbo frames on a VoIP/UC network are enabled, it can cause the same kind of delay to your network transmissions."

"VoIP uses will always not benefit from jumbo frame, as VoIP like gaming, is latency and time sensitive. Jumbo Frame for Internet Purpose: You will not see any performance boost as the files that came across the internet does not support jumbo frame."

<https://www.ankmax.com/newsinfo/1358641.html#:~:text=VoIP%20uses%20will%20always%20not,does%20n>

"To summarize this general best practice guide, you should NOT enable jumbo frame feature as a general home user."

**NEW QUESTION 346**

- (Exam Topic 3)

A network engineer is monitoring a fiber uplink to a remote office and notes the uplink has been operating at 100% capacity for a long duration. Which of the following performance metrics is MOST likely to be impacted with sustained link saturation?

- A. Latency
- B. Jitter
- C. Speed
- D. Bandwidth

**Answer: A**

**Explanation:**

When a fiber uplink is operating at 100% capacity for an extended period of time, it can cause sustained link saturation. This can impact the network's performance by increasing latency. Latency is the time it takes for a packet to travel from the source to its destination. When there is link saturation, packets may have to wait in a queue before being transmitted, which increases the time it takes for them to reach their destination. As a result, users may experience delays or timeouts when accessing network resources.

Other metrics such as jitter, speed, and bandwidth are also important, but they are not as directly impacted by sustained link saturation as latency.

**NEW QUESTION 350**

- (Exam Topic 3)

A company is designing a SAN and would like to use STP as its medium for communication. Which of the following protocols would BEST suit me company's needs?

- A. SFTP
- B. Fibre Channel
- C. iSCSI
- D. FTP

**Answer: B**

**Explanation:**

A SAN also employs a series of protocols enabling software to communicate or prepare data for storage. The most common protocol is the Fibre Channel Protocol (FCP), which maps SCSI commands over FC technology. The iSCSI SANs will employ an iSCSI protocol that maps SCSI commands over TCP/IP.

STP (Spanning Tree Protocol) is a protocol used to prevent loops in Ethernet networks, and it is not a medium for communication in a storage area network (SAN). However, Fibre Channel is a protocol that is specifically designed for high-speed data transfer in SAN environments. It is a dedicated channel technology that provides high throughput and low latency, making it ideal for SANs. Therefore, Fibre Channel would be the best protocol for the company to use for its SAN. SFTP (Secure File Transfer Protocol), iSCSI (Internet Small Computer System Interface), and FTP (File Transfer Protocol) are protocols used for transferring files over a network and are not suitable for use in a SAN environment.

#### NEW QUESTION 354

- (Exam Topic 3)

Which of the following OSI model layers is where a technician would view UDP information?

- A. Physical
- B. Data link
- C. Network
- D. Transport

**Answer:** D

#### NEW QUESTION 357

- (Exam Topic 3)

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

**Answer:** B

#### Explanation:

TACACS+ is used to authenticate users and authorize access to network resources. This protocol provides greater network security by encrypting the authentication credentials and reducing the risk of unauthorized access. According to the CompTIA Network+ Study Manual, "TACACS+ is an authentication protocol used to centralize authentication and authorization for network devices. It is a more secure alternative to Telnet for handling logins and for granting privileges to users."

#### NEW QUESTION 358

- (Exam Topic 3)

Which of the following is a security flaw in an application or network?

- A. A threat
- B. A vulnerability
- C. An exploit
- D. A risk

**Answer:** B

#### Explanation:

A vulnerability is a security flaw in an application or network that can be exploited by an attacker, allowing them to gain access to sensitive data or take control of the system. Vulnerabilities can range from weak authentication methods to unpatched software, allowing attackers to gain access to the system or data they would not otherwise be able to access. Exploits are programs or techniques used to take advantage of vulnerabilities, while threats are potential dangers, and risks are the likelihood of a threat becoming a reality.

#### NEW QUESTION 360

- (Exam Topic 3)

Which of the following describes the BEST device to configure as a DHCP relay?

- A. Bridge
- B. Router
- C. Layer 2 switch
- D. Hub

**Answer:** B

#### Explanation:

Normally, routers do not forward broadcast traffic. This means that each broadcast domain must be served by its own DHCP server. On a large network with multiple subnets, this would mean provisioning and configuring many DHCP servers. To avoid this scenario, a DHCP relay agent can be configured to provide forwarding of DHCP traffic between subnets. Routers that can provide this type of forwarding are described as RFC 1542 compliant. The DHCP relay intercepts broadcast DHCP frames, applies a unicast address for the appropriate DHCP server, and forwards them over the interface for the subnet containing the server. The DHCP server can identify the original IP subnet from the packet and offer a lease from the appropriate scope. The DHCP relay also performs the reverse process of directing responses from the server to the appropriate client subnet.

#### NEW QUESTION 361

- (Exam Topic 3)

An IT officer is installing a new WAP. Which of the following must the officer change to connect users securely to the WAP?

- A. AES encryption
- B. Channel to the highest frequency within the band
- C. TKIP encryption protocol
- D. Dynamic selection of the frequency

**Answer:** A

#### NEW QUESTION 366

- (Exam Topic 3)

A customer wants to log in to a vendor's server using a web browser on a laptop. Which of the following would require the LEAST configuration to allow encrypted access to the server?

- A. Secure Sockets Layer
- B. Site-to-site VPN
- C. Remote desktop gateway
- D. Client-to-site VPN

**Answer:** A

**Explanation:**

SSL is a widely used protocol for establishing secure, encrypted connections between devices over the Internet. It is typically used to secure communication between web browsers and servers, and can be easily enabled on a server by installing an SSL certificate.

**NEW QUESTION 371**

- (Exam Topic 3)

Which of the following provides guidance to an employee about restricting non-business access to the company's videoconferencing solution?

- A. Acceptable use policy
- B. Data loss prevention
- C. Remote access policy
- D. Standard operating procedure

**Answer:** A

**Explanation:**

An acceptable use policy (AUP) is a set of rules that outline the proper and improper use of an organization's resources, such as its videoconferencing solution. An AUP can provide guidance to employees about what is expected of them when using the organization's videoconferencing solution, including restricting non-business access to it.

**NEW QUESTION 373**

- (Exam Topic 3)

Which of the following protocols would enable a company to upgrade its internet connection by acquiring its own public IP prefixes and autonomous system number?

- A. EIGRP
- B. BGP
- C. IPv6
- D. MPLS

**Answer:** B

**Explanation:**

BGP is a routing protocol that is used to exchange routing information between different autonomous systems (ASes) on the internet. An autonomous system is a network or group of networks that is under the same administrative control and uses a common routing protocol. By acquiring its own public IP prefixes and autonomous system number, a company can use BGP to advertise these prefixes to other ASes and establish its own internet connection. This would enable the company to have more control over its internet connection and potentially improve its connectivity. EIGRP (Enhanced Interior Gateway Routing Protocol) is a routing protocol used within a single autonomous system, so it would not be used to establish a connection to the internet. IPv6 is a version of the Internet Protocol (IP) used to identify devices on a network. It is not a routing protocol and would not be used to establish an internet connection. MPLS (Multi-Protocol Label Switching) is a networking technology that is used to route packets between different networks. It is not a routing protocol and would not be used to establish an internet connection.

**NEW QUESTION 375**

- (Exam Topic 3)

Which of the following is the IEEE link cost for a Fast Ethernet interface in STP calculations?

- A. 2
- B. 4
- C. 19
- D. 100

**Answer:** D

**Explanation:**

The IEEE standard for link cost for a Fast Ethernet interface is 100, and for a Gigabit Ethernet interface is 19. These values are based on the bandwidth of the interface, with lower values indicating a higher-bandwidth interface.

**NEW QUESTION 380**

- (Exam Topic 3)

A network resource was accessed by an outsider as a result of a successful phishing campaign. Which of the following strategies should be employed to mitigate the effects of phishing?

- A. Multifactor authentication
- B. Single sign-on
- C. RADIUS
- D. VPN

**Answer:** A

**Explanation:**

Multifactor authentication is a security measure that requires users to provide multiple pieces of evidence before they can access a network resource. This could include requiring users to enter a username, password, and a code sent to the user's mobile phone before they are allowed access. This ensures that the user is who they say they are, reducing the risk of malicious actors gaining access to network resources as a result of a successful phishing campaign.

**NEW QUESTION 384**

- (Exam Topic 3)

A network technician is troubleshooting an application issue. The technician is able to recreate the issue in a virtual environment. According to the troubleshooting methodology, which of the following actions will the technician most likely perform NEXT?

- A. Gather information from the initial report.
- B. Escalate the issue to a supervisor.
- C. Implement a solution to resolve the issue.
- D. Establish a theory of probable cause.

**Answer:** D

**NEW QUESTION 387**

- (Exam Topic 3)

A technician is deploying a new SSID for an industrial control system. The control devices require the network to use encryption that employs TKIP and a symmetrical password to connect. Which of the following should the technician configure to ensure compatibility with the control devices?

- A. WPA2-Enterprise
- B. WPA-Enterprise
- C. WPA-PSK
- D. WPA2-PSK

**Answer:** C

**Explanation:**

"WPA uses Temporal Key Integrity Protocol (TKIP) for enhanced encryption. TKIP uses RC4 for the encryption algorithm, and the CompTIA Network+ exam may reference TKIP-RC4 in a discussion of wireless."

"WPA2 uses Counter Mode with Cipher Block Chaining Message Authentication Code

Protocol (CCMP) for integrity checking and Advanced Encryption Standard (AES) for encryption. On the Network+ exam, you might find this referenced as simply CCMP-AES"

**NEW QUESTION 391**

- (Exam Topic 3)

A network administrator installed an additional IDF during a building expansion project. Which of the following documents need to be updated to reflect the change? (Select TWO).

- A. Data loss prevention policy
- B. BYOD policy
- C. Acceptable use policy
- D. Non-disclosure agreement
- E. Disaster recovery plan
- F. Physical network diagram

**Answer:** BF

**NEW QUESTION 396**

- (Exam Topic 3)

A PC user who is on a local network reports very slow speeds when accessing files on the network server. The user's PC is connecting, but file downloads are very slow when compared to other users' download speeds. The PC's NIC should be capable of Gigabit Ethernet. Which of the following will MOST likely fix the issue?

- A. Releasing and renewing the PC's IP address
- B. Replacing the patch cable
- C. Reseating the NIC inside the PC
- D. Flushing the DNS cache

**Answer:** B

**Explanation:**

A slow download speed can be caused by a faulty patch cable, which is the cable used to connect the user's PC to the network server. If the patch cable is damaged, the connection will be slower than expected, resulting in slow download speeds. Replacing the patch cable is the most likely solution to this issue, as it will provide a new, reliable connection that should allow for faster download speeds.

**NEW QUESTION 399**

- (Exam Topic 3)

A technician was cleaning a storage closet and found a box of transceivers labeled 8Gbps. Which of the following protocols uses those transceivers?

- A. Coaxial over Ethernet
- B. Internet Small Computer Systems Interface
- C. Fibre Channel
- D. Gigabit interface converter

**Answer:** C

**Explanation:**

The transceivers labeled 8Gbps are likely to be used with the Fibre Channel protocol. Fibre Channel is a high-speed networking technology that is primarily used to connect storage devices to servers in storage area networks (SANs). It is capable of transmitting data at speeds of up to 8 Gbps (gigabits per second), and uses specialized transceivers to transmit and receive data over fiber optic cables.

Coaxial over Ethernet (CoE) is a networking technology that uses coaxial cables to transmit data, and is not related to the transceivers in question. Internet Small Computer Systems Interface (iSCSI) is a protocol that allows devices to communicate over a network using the SCSI protocol, and does not typically use specialized transceivers. Gigabit interface converter (GBIC) is a type of transceiver used to transmit and receive data over fiber optic cables, but it is not capable of transmitting data at 8 Gbps.

**NEW QUESTION 404**

- (Exam Topic 3)

A false camera is installed outside a building to assist with physical security. Which of the following is the device assisting?

- A. Detection
- B. Recovery
- C. Identification
- D. Prevention

**Answer:** A

**NEW QUESTION 408**

- (Exam Topic 3)

A network technician was hired to harden the security of a network. The technician is required to enable encryption and create a password for AP security through the web browser. Which of the following would BEST support these requirements?

- A. ESP
- B. WPA2
- C. IPSec
- D. ACL

**Answer:** B

**NEW QUESTION 410**

- (Exam Topic 3)

A technician installed an 8-port switch in a user's office. The user needs to add a second computer in the office, so the technician connects both PCs to the switch and connects the switch to the wall jack. However, the new PC cannot connect to network resources. The technician then observes the following:

- The new computer does not get an IP address on the client's VLAN.
- Both computers have a link light on their NICs.
- The new PC appears to be operating normally except for the network issue.
- The existing computer operates normally.

Which of the following should the technician do NEXT to address the situation?

- A. Contact the network team to resolve the port security issue.
- B. Contact the server team to have a record created in DNS for the new PC.
- C. Contact the security team to review the logs on the company's SIEM.
- D. Contact the application team to check NetFlow data from the connected switch.

**Answer:** A

**NEW QUESTION 411**

- (Exam Topic 3)

Which of the following protocols can be used to change device configurations via encrypted and authenticated sessions? (Select TWO).

- A. SNMPv3
- B. SSh
- C. Telnet
- D. IPSec
- E. ESP
- F. Syslog

**Answer:** BD

**NEW QUESTION 412**

- (Exam Topic 3)

An administrator is investigating reports of network slowness in a building. While looking at the uplink interface statistics in the switch's CLI, the administrator discovers the uplink is at 100% utilization. However, the administrator is unsure how to identify what traffic is causing the saturation. Which of the following tools should the administrator utilize to identify the source and destination addresses of the traffic?

- A. SNMP
- B. Traps
- C. Syslog
- D. NetFlow

**Answer:** D

**Explanation:**

To identify the source and destination addresses of the traffic causing network saturation, the network administrator should use a network protocol analyzer that supports the NetFlow protocol. NetFlow is a network protocol that collects IP traffic information as it enters or exits an interface and sends it to a NetFlow collector for analysis. This data includes the source and destination addresses of the traffic, the ports used, and the number of bytes and packets transferred.

Therefore, the correct answer is option D, NetFlow.

Reference: CompTIA Network+ Study Guide, Exam N10-007, Fourth Edition, by Todd Lammle (Chapter 6: Network Devices)

**NEW QUESTION 416**

- (Exam Topic 3)

A small office is running WiFi 4 APs, and neighboring offices do not want to increase the throughput to associated devices. Which of the following is the MOST cost-efficient way for the office to increase network performance?

- A. Add another AP.
- B. Disable the 2.4GHz radios.
- C. Enable channel bonding.
- D. Upgrade to WiFi 5.

**Answer: C**

**Explanation:**

Channel bonding is a practice commonly used in IEEE 802.11 implementations in which two adjacent channels within a given frequency band are combined to increase throughput between two or more wireless devices. Channel bonding is also known as Ethernet bonding, but it is used heavily in Wi-Fi implementations. It has become a very popular technique in the world of Wi-Fi because its increased throughput provides for more functionality within Wi-Fi deployments. Channel bonding is also known as NIC bonding. Source- <https://www.techopedia.com/definition/2999/channel-bonding>

**NEW QUESTION 417**

- (Exam Topic 3)

Which of the following commands can be used to display the IP address, subnet address, gateway address, and DNS address on a Windows computer?

- A. netstat -a
- B. ifconfig
- C. ip addr
- D. ipconfig /all

**Answer: D**

**Explanation:**

The ipconfig command is a utility that allows you to view and modify the network configuration of a Windows computer. By running the command "ipconfig /all", you can view detailed information about the network configuration of your computer, including the IP address, subnet mask, default gateway, and DNS server addresses.

Option A (netstat -a) is a command that displays active network connections and their status, but it does not display IP address or other network configuration information. Option B (ifconfig) is a command used on Linux and Unix systems to view and modify network configuration, but it is not available on Windows. Option C (ip addr) is a command used on Linux and Unix systems to view and modify network configuration, but it is not available on Windows.

**NEW QUESTION 421**

- (Exam Topic 3)

Which of the following ports are associated with IMAP? (Choose two.)

- A. 25
- B. 110
- C. 143
- D. 587
- E. 993
- F. 995

**Answer: CE**

**Explanation:**

Reference:

<https://billing.precedence.com.au/billing/knowledgebase/70/Mail-Ports-for-POP3-IMAP-and-SMTP.html>

**NEW QUESTION 425**

- (Exam Topic 3)

A company rents out a large event space and includes wireless internet access for each tenant. Tenants reserve a two-hour window from the company each week, which includes a tenant-specific SSID. However, all users share the company's network hardware.

Wireless encryption	WPA2
Captive portal	Disabled
AP isolation	Enabled
Subnet mask	255.255.255.0
DNS server	10.0.0.1
Default gateway	10.1.10.1
DHCP scope begin	10.1.10.10
DHCP scope end	10.1.10.150
DHCP lease time	24 hours

The network support team is receiving complaints from tenants that some users are unable to connect to the wireless network. Upon investigation, the support teams discover a pattern indicating that after a tenant with a particularly large attendance ends its sessions, tenants throughout the day are unable to connect.

The following settings are common to all network configurations:  
Which of the following actions would MOST likely reduce this Issue? (Select TWO).

- A. Change to WPA encryption
- B. Change the DNS server to 10.1.10.1.
- C. Change the default gateway to 10.0.0.1.
- D. Change the DHCP scope end to 10.1.10.250
- E. Disable AP isolation
- F. Change the subnet mask to 255.255.255.192.
- G. Reduce the DHCP lease time to four hours.

**Answer:** DG

#### NEW QUESTION 430

- (Exam Topic 3)

A device is connected to a managed Layer 3 network switch. The MAC address of the device is known, but the static IP address assigned to the device is not. Which of the following features of a Layer 3 network switch should be used to determine the IPv4 address of the device?

- A. MAC table
- B. Neighbor Discovery Protocol
- C. ARP table
- D. IPConfig
- E. ACL table

**Answer:** C

#### Explanation:

The ARP table is a database that is used by a device to map MAC addresses to their corresponding IP addresses. When a device sends a packet to another device on the same network, it uses the MAC address of the destination device to deliver the packet. The ARP table allows the device to determine the IP address of the destination device based on its MAC address.

#### NEW QUESTION 435

- (Exam Topic 3)

A technician needs to configure a routing protocol for an internet-facing edge router. Which of the following routing protocols will the technician MOST likely use?

- A. BGP
- B. RIPv2
- C. OSPF
- D. EIGRP

**Answer:** A

#### NEW QUESTION 439

- (Exam Topic 3)

A network technician reviews an entry on the syslog server and discovers the following message from a switch:

SPANNING-TREE Port 1/1 BLOCKED

Which of the following describes the issue?

- A. A loop was discovered, and the impact was mitigated.
- B. An incorrectly pinned cable was disconnected.
- C. The link-local address on the port is incorrect.
- D. The port was shut down, and it needs to be reactivated.

**Answer:** A

#### NEW QUESTION 443

- (Exam Topic 3)

A network technician is troubleshooting a network issue for employees who have reported issues with speed when accessing a server in another subnet. The server is in another building that is 410ft (125m) away from the employees' building. The 10GBASE-T connection between the two buildings uses Cat 5e. Which of the following BEST explains the speed issue?

- A. The connection type is not rated for that distance
- B. A broadcast storm is occurring on the subnet.
- C. The cable run has interference on it
- D. The connection should be made using a Cat 6 cable

**Answer:** D

#### Explanation:

The 10GBASE-T connection between the two buildings uses Cat 5e, which is not rated for a distance of 410ft (125m). According to the CompTIA Network+ Study Manual, for 10GBASE-T connections, "Cat 5e is rated for up to 55m, Cat 6a is rated for 100m, and Cat 7 is rated for 150m." Therefore, the speed issue is likely due to the fact that the connection type is not rated for the distance between the two buildings. To resolve the issue, the technician should consider using a Cat 6a or Cat 7 cable to increase the distance the connection is rated for.

#### NEW QUESTION 444

- (Exam Topic 3)

A network technician receives a report about a performance issue on a client PC that is connected to port 1/3 on a network switch. The technician observes the following configuration output from the switch:

1/1	Client PC	Connected	Full	1000
1/2	Client PC	Connected	Full	1000
1/3	Client PC	Connected	Full	10

Which of the following is a cause of the issue on port 1/3?

- A. Speed
- B. Duplex
- C. Errors
- D. VLAN

**Answer: A**

**NEW QUESTION 448**

- (Exam Topic 3)

Which of the following is used to provide disaster recovery capabilities to spin up an critical devices using internet resources?

- A. Cloud site
- B. Hot site
- C. Cold site
- D. Warm site

**Answer: A**

**NEW QUESTION 453**

- (Exam Topic 3)

A network administrator is planning a WLAN for a soccer stadium and was advised to use MU-MIMO to improve connection performance in high-density areas. The project requires compatibility with clients connecting using 2.4GHz or 5GHz frequencies. Which of the following would be the BEST wireless standard for this project?

- A. 80211ac
- B. 802.11ax
- C. 802.11g
- D. 80211n

**Answer: B**

**NEW QUESTION 457**

- (Exam Topic 3)

Which of the following is a benefit of the spine-and-leaf network topology?

- A. Increased network security
- B. Stable network latency
- C. Simplified network management
- D. Eliminated need for inter-VLAN routing

**Answer: A**

**NEW QUESTION 459**

- (Exam Topic 3)

An employee reports to a network administrator that internet access is not working. Which of the following should the administrator do FIRST?

- A. Establish a theory of probable cause.
- B. Identify symptoms.
- C. Determine if anything has changed.
- D. Ask the user to restart the computer.

**Answer: C**

**Explanation:**

When a user reports that internet access is not working, it is important to first determine if there have been any recent changes to the network or the user's computer that could have caused the issue. This could include changes to the network configuration, the installation of new software or hardware, or other events that could have impacted the user's ability to access the internet. By determining if anything has changed, the administrator can narrow down the possible causes of the issue and focus on addressing the most likely cause.

**NEW QUESTION 463**

- (Exam Topic 3)

A network engineer is investigating reports of poor network performance. Upon reviewing a report, the engineer finds hundreds of CRC errors on an interface. Which of the following is the MOST likely cause of these errors?

- A. A bad wire on the Cat 5e cable
- B. The wrong VLAN assignment to the switchport
- C. A misconfigured QoS setting on the router
- D. Both sides of the switch trunk set to full duplex

**Answer:** A

**NEW QUESTION 468**

- (Exam Topic 3)

Which of the following would be used when connecting devices that have different physical characteristics?

- A. A proxy server
- B. An industrial control system
- C. A load balancer
- D. A media converter

**Answer:** D

**NEW QUESTION 471**

- (Exam Topic 3)

The lack of a formal process to grant network permissions to different profiles of employees and contractors is leading to an increasing number of security incidents. Non-uniform and overly permissive network accesses are being granted. Which of the following would be the MOST appropriate method to improve the security of the environment?

- A. Change the default permissions to implicit deny
- B. Configure uniform ACLs to employees and NAC for contractors.
- C. Deploy an RDP server to centralize the access to the network
- D. Implement role-based access control

**Answer:** D

**Explanation:**

The most appropriate method to improve the security of the environment would be to implement role-based access control (RBAC). With RBAC, users are granted access to the network based on their role within the organization. This allows for more granular access control, as different roles may require different levels of access. Additionally, this ensures that users only have access to the resources they need and no more. This helps to reduce the risk of unauthorized access or misuse of the network. References and further information can be found in the CompTIA Network+ Study Manual, Chapter 8, Access Control.

RBAC is a method of restricting network access based on the roles of individual users within the organization. With RBAC, users are granted access only to the resources they need to perform their specific job functions. This approach reduces the risk of unauthorized access, provides greater visibility into user activity, and simplifies network management.

Changing the default permissions to implicit deny may improve security, but it could also cause issues for legitimate users who require access to specific resources. Configuring uniform ACLs and NAC for contractors is a step in the right direction, but it may not be enough to address the overall lack of a formal process for granting network permissions. Deploying an RDP server to centralize access to the network is not a viable solution, as it would not address the root cause of the security incidents.

Therefore, the most appropriate option is to implement role-based access control. Reference: CompTIA Network+ Study Guide, Fourth Edition, Chapter 7, section 7.4.

**NEW QUESTION 474**

- (Exam Topic 3)

On a network with redundant switches, a network administrator replaced one of the switches but was unable to get a connection with another switch. Which of the following should the administrator check after successfully testing the cable that was wired for TIA/EIA-568A on both ends?

- A. If MDIX is enabled on the new switch
- B. If PoE is enabled
- C. If a plenum cable is being used
- D. If STP is disabled on the switches

**Answer:** A

**Explanation:**

Auto-MDIX (or medium dependent interface crossover) is a feature that automatically detects the type of cable connection and configures the interface accordingly (i.e. straight-through or crossover). This ensures that the connection between the two switches is successful. This is referenced in the CompTIA Network+ Study Manual, page 519.

**NEW QUESTION 478**

- (Exam Topic 3)

Which of the following would be used to adjust resources dynamically for a virtual web server under variable loads?

- A. Elastic computing
- B. Scalable networking
- C. Hybrid deployment
- D. Multitenant hosting

**Answer:** B

**Explanation:**

A technique used to adjust resources dynamically for a virtual web server under variable loads is called auto-scaling. Auto-scaling automatically increases or decreases the number of instances of a virtual web server in response to changes in demand, ensuring that the right amount of resources are available to handle incoming traffic. This can help to improve the availability and performance of a web application, as well as reduce costs by avoiding the need to provision and maintain excess capacity.

**NEW QUESTION 479**

- (Exam Topic 3)

Which of the following would be used to forward requests and replies between a DHCP server and client?

- A. Relay
- B. Lease
- C. Scope
- D. Range

**Answer:** A

#### NEW QUESTION 481

- (Exam Topic 3)

A network team is getting reports that air conditioning is out in an IDF. The team would like to determine whether additional network issues are occurring. Which of the following should the network team do?

- A. Confirm that memory usage on the network devices in the IDF is normal.
- B. Access network baseline data for references to an air conditioning issue.
- C. Verify severity levels on the corporate syslog server.
- D. Check for SNMP traps from a network device in the IDF.
- E. Review interface statistics looking for cyclic redundancy errors.

**Answer:** D

#### Explanation:

"Baselines play an integral part in network documentation because they let you monitor the network's overall performance. In simple terms, a baseline is a measure of performance that indicates how hard the network is working and where network resources are spent. The purpose of a baseline is to provide a basis of comparison. For example, you can compare the network's performance results taken in March to results taken in June, or from one year to the next. More commonly, you would compare the baseline information at a time when the network is having a problem to information recorded when the network was operating with greater efficiency. Such comparisons help you determine whether there has been a problem with the network, how significant that problem is, and even where the problem lies."

#### NEW QUESTION 485

- (Exam Topic 3)

A technician is monitoring a network interface and notices the device is dropping packets. The cable and interfaces, however, are in working order. Which of the following is MOST likely the cause?

- A. OID duplication
- B. MIB mismatch
- C. CPU usage
- D. Encapsulation errors

**Answer:** C

#### NEW QUESTION 488

- (Exam Topic 3)

A malicious user is using special software to perform an on-path attack. Which of the following best practices should be configured to mitigate this threat?

- A. Dynamic ARP inspection
- B. Role-based access
- C. Control plane policing
- D. MAC filtering

**Answer:** A

#### NEW QUESTION 493

- (Exam Topic 3)

A network device needs to discover a server that can provide it with an IPv4 address. Which of the following does the device need to send the request to?

- A. Default gateway
- B. Broadcast address
- C. Unicast address
- D. Link local address

**Answer:** B

#### Explanation:

The DHCP client sends broadcast request packets to the network; the DHCP servers respond with broadcast packets that offer IP parameters, such as an IP address for the client. After the client chooses the IP parameters, communication between the client and server is by unicast packets.

"When a DHCP client boots up, it automatically sends out a DHCP Discover UDP datagram to the broadcast address, 255.255.255.255. This DHCP Discover message asks "Are there any DHCP servers out there?" The client can't send unicast traffic yet, as it doesn't have a valid IP address that can be used."

#### NEW QUESTION 498

- (Exam Topic 3)

Which of the following physical security methods is the MOST effective to prevent tailgating?

- A. Biometrics in an access control vestibule
- B. IP cameras with motion detection
- C. Smart lockers with tamper protection
- D. Badge readers plus a PIN pad

**Answer:** A

#### NEW QUESTION 502

- (Exam Topic 3)

A Chief Executive Officer and a network administrator came to an agreement With a vendor to purchase new equipment for the data center A document was drafted so all parties would be Informed about the scope of the project before It started. Which of the following terms BEST describes the document used?

- A. Contract
- B. Project charter
- C. Memorandum of understanding
- D. Non-disclosure agreement

**Answer: B**

#### Explanation:

The document used to inform all parties about the scope of the project before it starts is likely a project charter. A project charter is a document that outlines the key aspects of a project, including the project's objectives, scope, stakeholders, and resources. It serves as a formal agreement between the project team and the stakeholders, and helps to define the project's goals and constraints.

A project charter typically includes information about the project's scope, including the specific deliverables that are expected and any constraints or limitations that may impact the project. It may also include details about the project team and stakeholders, the project schedule and budget, and the roles and responsibilities of each party.

By creating a project charter, the Chief Executive Officer and the network administrator can ensure that all parties involved in the project have a clear understanding of the project's goals and objectives, and can help to prevent misunderstandings or miscommunications during the project.

What is in a project charter?

A project charter is a formal short document that states a project exists and provides project managers with written authority to begin work. A project charter document describes a project to create a shared understanding of its goals, objectives and resource requirements before the project is scoped out in detail.

What are the 5 elements of the project charter?

What Are the Contents of a Project Charter? A project charter should always include an overview, an outline of scope, an approximate schedule, a budget estimate, anticipated risks, and key stakeholders

#### NEW QUESTION 504

- (Exam Topic 3)

A technician is contracted to install a redundant cluster of devices from the ISP In case of a hardware failure within the network. Which of the following would provide the BEST redundant solution in Layer 2 devices?

- A. Multiple routers
- B. Multiple switches
- C. Multiple firewalls
- D. Multiple budges

**Answer: B**

#### NEW QUESTION 506

- (Exam Topic 3)

Users attending security training at work are advised not to use single words as passwords for corporate applications. Which of the following does this BEST protect against?

- A. An on-path attack
- B. A brute-force attack
- C. A dictionary attack
- D. MAC spoofing
- E. Denial of service

**Answer: C**

#### NEW QUESTION 508

- (Exam Topic 3)

A network administrator is trying to add network redundancy for the server farm. Which of the following can the network administrator configure to BEST provide this capability?

- A. VRRP
- B. DNS
- C. UPS
- D. RPO

**Answer: A**

#### Explanation:

VRRP is an open standard protocol, which is used to provide redundancy in a network. It is a network layer protocol (protocol number-112). The number of routers (group members) in a group acts as a virtual logical router which will be the default gateway of all the local hosts. If one router goes down, one of the other group members can take place for the responsibilities for forwarding the traffic.

#### NEW QUESTION 511

- (Exam Topic 3)

Logs show an unauthorized IP address entering a secure part of the network every night at 8:00 pm. The network administrator is concerned that this IP address will cause an issue to a critical server and would like to deny the IP address at the edge of the network. Which of the following solutions would address these concerns?

- A. Changing the VLAN of the web server
- B. Changing the server's IP address

- C. Implementing an ACL
- D. Instating a rule on the firewall connected to the web server

**Answer:** D

**NEW QUESTION 512**

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### N10-008 Practice Exam Features:

- \* N10-008 Questions and Answers Updated Frequently
- \* N10-008 Practice Questions Verified by Expert Senior Certified Staff
- \* N10-008 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* N10-008 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The N10-008 Practice Test Here](#)**