

Exam Questions EX200

EX200 Red Hat Certified System Administrator (RHCSA) Exam

<https://www.2passeasy.com/dumps/EX200/>



NEW QUESTION 1

CORRECT TEXT

Create a swap space, set the size is 600 MB, and make it be mounted automatically after rebooting the system (permanent mount).

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? if=/dev/zero of=/swapfile bs=1M count=600 mkswap /swapfile
/etc/fstab:
/swapfile swap swap defaults 0 0 mount -a
```

NEW QUESTION 2

CORRECT TEXT

Part 1 (on Node1 Server)

Task 9 [Managing Files from the Command Line]

Search the string nologin in the /etc/passwd file and save the output in /root/strings

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
*
[root@node1 ~]# cat /etc/passwd | grep nologin > /root/strings
[root@node1 ~]# cat /root/strings
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
adm:x:3:4:adm:/var/adm:/sbin/nologin lp:x:4:7:
lp:/var/spool/lpd:/sbin/nologin
mail:x:8:12:mail:/var/spool/mail:/sbin/nologin
```

NEW QUESTION 3

CORRECT TEXT

Create a backup

Create a backup file named /root/backup.tar.bz2, contains the content of /usr/local, tar must use bzip2 to compress.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
cd /usr/local
tar -jcvf /root/backup.tar.bz2
mkdir /test
tar -jxvf /root/backup.tar.bz2 -C /test// Decompression to check the content is the same as the /usr/loca after
If the questions require to use gzip to compress. change -j to -z.
```

NEW QUESTION 4

CORRECT TEXT

Create the user named eric and deny to interactive login.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? useradd eric
? passwd eric
? vi /etc/passwd
? eric:x:505:505::/home/eric:/sbin/nologin
```

Which shell or program should start at login time is specified in /etc/passwd file? By default, Redhat Enterprise Linux assigns the /bin/bash shell to the users. To deny the interactive login, you should write /sbin/nologin or /bin/ false instead of login shell.

NEW QUESTION 5

CORRECT TEXT

The firewall must be open.

- A. Mastered
- B. Not Mastered

Answer:

A

Explanation:

```
/etc/init.d/iptables start
iptables -F
iptables -X
iptables -Z
/etc/init.d/iptables save
chkconfig iptables on
```

NEW QUESTION 6

CORRECT TEXT

Some users home directory is shared from your system. Using showmount -e localhost command, the shared directory is not shown. Make access the shared users home directory.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? Verify the File whether Shared or not ? : cat /etc/exports
? Start the nfs service: service nfs start
? Start the portmap service: service portmap start
? Make automatically start the nfs service on next reboot: chkconfig nfs on
? Make automatically start the portmap service on next reboot: chkconfig portmap on
? Verify either sharing or not: showmount -e localhost
? Check that default firewall is running on system?
If running flush the iptables using iptables -F and stop the iptables service.
```

NEW QUESTION 7

CORRECT TEXT

Configure autofs to automount the home directories of LDAP users as follows: host.domain11.example.com NFS-exports /home to your system.

This filesystem contains a pre-configured home directory for the user ldapuser11 ldapuser11's home directory is host.domain11.example.com /rhome/ldapuser11

ldapuser11's home directory should be automounted locally beneath /rhome as

/rhome/ldapuser11

Home directories must be writable by their users ldapuser11's password is 'password'.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? vim /etc/auto.master /rhome /etc/auto.misc
wq!
# vim /etc/auto.misc
ldapuser11 --rw,sync host.domain11.example.com:/rhome/ldpauser11 :wq!
#service autofs restart
? service autofs reload
? chkconfig autofs on
? su -ldapuser11
Login ldapuser with home directory
# exit
```

NEW QUESTION 8

CORRECT TEXT

Who ever creates the files/directories on archive group owner should be automatically should be the same group owner of archive.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? chmod g+s /archive
? Verify using: ls -ld /archive Permission should be like:
drwxrws--- 2 root sysuser 4096 Mar 16 18:08 /archive
If SGID bit is set on directory then who every users creates the files on directory group owner automatically the owner of parent directory.
To set the SGID bit: chmod g+s directory
To Remove the SGID bit: chmod g-s directory
```

NEW QUESTION 9

CORRECT TEXT

Download the document from ftp://instructor.example.com/pub/testfile, find all lines containing [abcde] and redirect to /MNT/answer document, then rearrange the order according the original content.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Download the file to /tmp first
grep [abcde] /tmp/testfile > /mnt/answer

NEW QUESTION 10

CORRECT TEXT

Configure autofs.

Configure the autofs automatically mount to the home directory of LDAP, as required: server.domain11.example.com use NFS to share the home to your system.

This file system

contains a pre

configured home directory of user ldapuserX. Home directory of ldapuserX is:

server.domain11.example.com /home/guests/ldapuser

Home directory of ldapuserX should automatically mount to the ldapuserX of the local

/home/guests Home directory's write permissions must be available for users ldapuser1's password is password

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

yum install -y autofs

mkdir /home/rehome

? /etc/auto.master

/home/rehome/etc/auto.ldap

Keep then exit

cp /etc/auto.misc /etc/auto.ldap

? /etc/auto.ldap

ldapuserX -fstype=nfs,rw server.domain11.example.com:/home/guests/

Keep then exit

systemctl start autofs

systemctl enable autofs

su - ldapuserX// test

If the above solutions cannot create files or the command prompt is -bash-4.2\$, it maybe exist multi-level directory, this needs to change the

server.domain11.example.com:/home/guests/ to server.domain11.example.com:/home/guests/ldapuserX. What is multi-level directory? It means there is a

directory of ldapuserX under the /home/guests/ldapuserX in the questions. This directory is the real directory.

NEW QUESTION 10

CORRECT TEXT

One Package named zsh is dump on ftp://server1.example.com under /pub/updates directory and your FTP server is 192.168.0.254. Install the package zsh.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

? rpm -ivh ftp://server1/example.com/pub/updates/zsh-* or

? Login to ftp server : ftp ftp://server1.example.com using anonymous user.

? Change the directory: cd pub and cd updates

? Download the package: mget zsh-*

? Quit from the ftp prompt : bye

? Install the package

? rpm -ivh zsh-*

? Verify either package is installed or not : rpm -q zsh

NEW QUESTION 11

CORRECT TEXT

A YUM source has been provided in the http://instructor.example.com/pub/rhel6/dvd Configure your system and can be used normally.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

? /etc/yum.repos.d/base.repo

[base] name=base

baseurl=http://instructor.example.com/pub/rhel6/dvd

gpgcheck=0

yum list

NEW QUESTION 15

CORRECT TEXT

Find the files owned by harry, and copy it to catalog: /opt/dir

- A. Mastered

B. Not Mastered

Answer: A

Explanation:

```
# cd /opt/  
# mkdir dir  
# find / -user harry -exec cp -rfp {} /opt/dir/ \;
```

NEW QUESTION 18

CORRECT TEXT

Configure the system synchronous as 172.24.40.10.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical Interfaces:
System-->Administration-->Date & Time
OR
system-config-date

NEW QUESTION 20

CORRECT TEXT

Create a user named alex, and the user id should be 1234, and the password should be alex111.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# useradd -u 1234 alex  
# passwd alex  
alex111  
alex111  
OR  
echo alex111|passwd -stdin alex
```

NEW QUESTION 25

CORRECT TEXT

According the following requirements, configure autofs service and automatically mount to user's home directory in the ldap domain.

- Instructor.example.com (192.168.0.254) has shared /home/guests/ldapuserX home directory to your system by over NFS export, X is your hostname number.
- LdapuserX's home directory is exist in the instructor.example.com: /home/ guests/ldapuserX
- LdapuserX's home directory must be able to automatically mount to /home/ guests/ldapuserX in your system.
- Home directory have write permissions for the corresponding user.

However, you can log on to the ldapuser1 - ldapuser99 users after verification. But you can only get your corresponding ldapuser users. If your system's hostname is server1.example.com, you can only get ldapuser1's home directory.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
mkdir -p /home/guests  
cat /etc/auto.master:  
/home/guests /etc/auto.ldap  
cat /etc/auto.ldap:  
ldapuser1 -rw instructor.example.com:/home/guests/ldapuser1  
? automatically mount all the user's home directory #* -rw  
instructor.example.com:/home/guests/&
```

NEW QUESTION 30

CORRECT TEXT

Create User Account.

Create the following user, group and group membership:

Adminuser group

User natasha, using adminuser as a sub group

User Harry, also using adminuser as a sub group

User sarah, can not access the SHELL which is interactive in the system, and is not a member of adminuser, natashaharrysarah password is redhat.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
groupadd adminuser
useradd natasha -G adminuser
useradd haryy -G adminuser
useradd sarah -s /sbin/nologin
Passwd user name // to modify password or echo redhat | passwd --stdin user name id natasha // to view user group.
```

NEW QUESTION 31

CORRECT TEXT

Add 3 users: harry, natasha, tom.

The requirements: The Additional group of the two users: harry, Natasha is the admin group. The user: tom's login shell should be non-interactive.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# useradd -G admin harry
# useradd -G admin natasha
# useradd -s /sbin/nologin tom
# id harry;id Natasha (Show additional group)
# cat /etc/passwd (Show the login shell)
OR
# system-config-users
```

NEW QUESTION 35

CORRECT TEXT

We are working on /data initially the size is 2GB. The /dev/test0/lvtestvolume is mount on /data. Now you required more space on /data but you already added all disks belong to physical volume. You saw that you have unallocated space around 5 GB on your harddisk. Increase the size of lvtestvolume by 5GB.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? Create a partition having size 5 GB and change the systid '8e'.
? use partprobe command
? pvcreate /dev/hda9 Suppose your partition number is hda9.
? vgextend test0 /dev/hda9 vgextend command add the physical disk on volume group.
? lvextend -L+5120M /dev/test0/lvtestvolume
? verify using lvdisplay /dev/test0/lvtestvolume.
```

NEW QUESTION 39

CORRECT TEXT

Part 1 (on Node1 Server)

Task 14 [Managing SELinux Security]

You will configure a web server running on your system serving content using a non- standard port (82)

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
*
[root@node1 ~]# curl http://node1.domain15.example.com
curl: (7) Failed to connect to node1.domain15.example.com port 80: Connection refused
[root@node1 ~]# yum install httpd
[root@node1 ~]# systemctl enable --now httpd
Created symlink /etc/systemd/system/multi-user.target.wants/httpd.service
/usr/lib/systemd/system/httpd.service.
[root@node1 ~]# systemctl start httpd
[root@node1 ~]# systemctl status httpd
Status: "Running, listening on: port 80"
*

[root@node1 ~]# wget http://node1.domain15.example.com
2021-03-23 13:27:28 ERROR 403: Forbidden.
[root@node1 ~]# semanage port -l | grep http
http_port_t tcp 80, 81, 443, 488, 8008, 8009, 8443, 9000
[root@node1 ~]# semanage port -a -t http_port_t -p tcp 82
[root@node1 ~]# semanage port -l | grep http
http_port_t tcp 82, 80, 81, 443, 488, 8008, 8009, 8443, 9000
[root@node1 ~]# firewall-cmd --zone=public --list-all
[root@node1 ~]# firewall-cmd --permanent --zone=public --add-port=82/tcp
[root@node1 ~]# firewall-cmd --reload
[root@node1 ~]# curl http://node1.domain15.example.com
OK
```



```
*
root@node1 ~]# wget http://node1.domain15.example.com:82
Connection refused.
[root@node1 ~]# vim /etc/httpd/conf/httpd.conf Listen 82
[root@node1 ~]# systemctl restart httpd
[root@node1 ~]# wget http://node1.domain15.example.com:82
2021-03-23 13:31:41 ERROR 403: Forbidden.
[root@node1 ~]# curl http://node1.domain15.example.com:82
OK
```

NEW QUESTION 42

CORRECT TEXT

Part 2 (on Node2 Server)

Task 4 [Managing Logical Volumes]

Resize the logical volume, lvrz and reduce filesystem to 4600 MiB. Make sure the the filesystem contents remain intact with mount point /datarz

(Note: partitions are seldom exactly the size requested, so anything within the range of 4200MiB to 4900MiB is acceptable)

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
*
[root@node2 ~]# lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
vdb 252:16 0 5G 0 disk
vdb1 252:17 0 4.2G 0 part
vgrz-lvrz 253:2 0 4.1G 0 lvm /datarz
vdc 252:32 0 5G 0 disk
vdc1 252:33 0 4.4G 0 part
datavg-data1v 253:3 0 3.9G 0 lvm /data
vdd 252:48 0 5G 0 disk
vde 252:64 0 10G 0 disk
[root@node2 ~]# lvs
LV VG Attr LSize Pool Origin Data% Meta% Move Log Cpy%Sync Convert
lvrz vgrz -wi-ao---- 4.10g
[root@node2 ~]# vgs
VG #PV #LV #SN Attr VSize VFree
vgrz 1 1 0 wz--n- <4.15g 48.00m
[root@node2 ~]# parted /dev/vdb print
Number Start End Size Type File system Flags
1 1049kB 4456MB 4455MB primary lvm
*
[root@node2 ~]# df -hT
Filesystem Type Size Used Avail Use% Mounted on
/dev/mapper/vgrz-lvrz ext4 4.0G 17M 3.8G 1% /datarz
[root@node2 ~]# parted /dev/vdb mkpart primary 4456MiB 5100MiB
[root@node2 ~]# parted /dev/vdb set 2 lvm on
[root@node2 ~]# udevadm settle
[root@node2 ~]# pvcreate /dev/vdb2
Physical volume "/dev/vdb2" successfully created.
*
[root@node2 ~]# vgextend vgrz /dev/vdb2
Volume group "vgrz" successfully extended
[root@node2 ~]# lvextend -r -L 4600M /dev/vgrz/lvrz
Size of logical volume vgrz/lvrz changed from 4.10 GiB (1050 extents) to 4.49 GiB (1150 extents).
Logical volume vgrz/lvrz successfully resized.
[root@node2 ~]# resize2fs /dev/vgrz/lvrz
[root@node2 ~]# df -hT
Filesystem Type Size Used Avail Use% Mounted on
/dev/mapper/vgrz-lvrz ext4 4.4G 17M 4.2G 1% /datarz
```

NEW QUESTION 43

CORRECT TEXT

Add a swap partition.

Adding an extra 500M swap partition to your system, this swap partition should mount automatically when the system starts up. Don't remove and modify the existing swap partitions on your system.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

fdisk -cu /dev/vda// in the way of expanding the partition, don't make main partition

partx -a /dev/vda

mkswap /dev/vdax

swapon /dev/vdax

swapon -s

vi /etc/fstab

/dev/vdaxswapswapdefaults0 0
mount -a

NEW QUESTION 47

CORRECT TEXT

Part 1 (on Node1 Server)

Task 6 [Accessing Linux File Systems]

Find all lines in the file /usr/share/mime/packages/freedesktop.org.xml that contain the string ich.

Put a copy of these lines in the original order in the file /root/lines.

/root/lines should contain no empty lines and all lines must be exact copies of the original lines in

/usr/share/mime/packages/freedesktop.org.xml

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

*

```
[root@node1 ~]# cat /usr/share/mime/packages/freedesktop.org.xml | grep ich > /root/lines
```

```
[root@node1 ~]# cat /root/lines
```

```
<comment xml:lang="ast">Ficheru codificáu en BinHex de Machintosh</comment>
```

```
<comment xml:lang="fr">fichier codé Macintosh BinHex</comment>
```

```
<comment xml:lang="gl">ficheiro de Macintosh codificado con BinHex</comment>
```

```
<comment xml:lang="oc">fichièr encodat Macintosh BinHex</comment>
```

```
<comment xml:lang="pt">ficheiro codificado em BinHex de Macintosh</comment>
```

```
<comment xml:lang="fr">fichier boîte aux lettres</comment>
```

NEW QUESTION 52

CORRECT TEXT

Who ever creates the files/directories on a data group owner should automatically be in the same group owner as data.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

* 1. chmod g+s /data

* 2. Verify using: ls -ld /data

Permission should be like this: drwxrws--- 2 root sysadmin 4096 Mar 16 18:08 /data

If SGID bit is set on directory then who every users creates the files on directory group owner automatically the owner of parent directory. To set the SGID bit:

chmod g+s directory To Remove the SGID bit: chmod g-s directory

NEW QUESTION 53

CORRECT TEXT

Search files.

Find out files owned by jack, and copy them to directory /root/findresults

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

mkdir/root/findfiles

find / -user jack -exec cp -a {} /root/findfiles/ \; ls /root/findresults

NEW QUESTION 55

CORRECT TEXT

Configure iptables, there are two domains in the network, the address of local domain is 172.24.0.0/16 other domain is 172.25.0.0/16, now refuse domain 172.25.0.0/16 to access the server.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

below

? iptables -F

? service iptables save

? iptables -A INPUT -s 172.25.0.0/16 -j REJECT

? service iptables save

? service iptables restart

NEW QUESTION 58

CORRECT TEXT

Part 2 (on Node2 Server)

Task 7 [Implementing Advanced Storage Features]

Create a thin-provisioned filesystem with the name think_fs from a pool think_pool using the devices.

The filesystem should be mounted on /strav and must be persistent across reboot

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

*

```
[root@node2 ~]# lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
vdd 252:48 0 5G 0 disk
vde 252:64 0 10G 0 disk
vdo1 253:4 0 50G 0 vdo /vbreadd
[root@node2 ~]# yum install stratis* -y
[root@node2 ~]# systemctl enable --now stratisd.service
[root@node2 ~]# systemctl start stratisd.service
[root@node2 ~]# systemctl status stratisd.service
[root@node2 ~]# stratis pool create think_pool /dev/vdd
[root@node2 ~]# stratis pool list
Name Total Physical Properties
think_pool 5 GiB / 37.63 MiB / 4.96 GiB ~Ca,~Cr
*
[root@node2 ~]# stratis filesystem create think_pool think_fs
[root@node2 ~]# stratis filesystem list
Pool Name Name Used Created Device UUID
think_pool think_fs 546 MiB Mar 23 2021 08:21 /stratis/think_pool/think_fs ade6fdaab06449109540c2f3fdb9417d
[root@node2 ~]# mkdir /strav
[root@node2 ~]# lsblk
[root@node2 ~]# blkid
/dev/mapper/stratis-1-91ab9faf36a540f49923321ba1c5e40d-thin-fs- ade6fdaab06449109540c2f3fdb9417d: UUID="ade6fdaa-b064-4910-9540-c2f3fdb9417d"
BLOCK_SIZE="512" TYPE="xfs"
*
[root@node2 ~]# vim /etc/fstab
UUID=ade6fdaa-b064-4910-9540-c2f3fdb9417d /strav xfs defaults,x- systemd.requires=stratisd.service 0 0
[root@node2 ~]# mount /stratis/think_pool/think_fs /strav/
[root@node2 ~]# df -hT
/dev/mapper/stratis-1-91ab9faf36a540f49923321ba1c5e40d-thin-fs- ade6fdaab06449109540c2f3fdb9417d xfs 1.0T 7.2G 1017G 1% /strav
```

NEW QUESTION 60

CORRECT TEXT

Make on data that only the user owner and group owner member can fully access.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? chmod 770 /data
? Verify using : ls -ld /data Preview should be like:
drwxrwx--- 2 root sysadmin 4096 Mar 16 18:08 /data
To change the permission on directory we use the chmod command.
According to the question that only the owner user (root) and group member (sysadmin) can fully access the directory so: chmod 770 /data
```

NEW QUESTION 64

CORRECT TEXT

The system ldap.example.com provides an LDAP authentication service.

Your system should bind to this service as follows:

The base DN for the authentication service is dc=domain11, dc=example, dc=com LDAP is used to provide both account information and authentication information. The connection should be encrypted using the certificate at http://host.domain11.example.com/pub/domain11.crt

When properly configured, ldapuserX should be able to log into your system, but will not have a home directory until you have completed the autofs requirement.

Username: ldapuser11

Password: password

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
? system-config-authentication LDAP user DN=dc=domain11,dc=example,dc=com Server= host.domain11.example.com
Certificate= http://host.domain11.example.com/pub/domain11.crt (enter url carefully, there maybe // or ..)
LDAP password
OK
starting sssd
? su -ldapuser11 Display Bash prompt #exit
```

NEW QUESTION 69

CORRECT TEXT

Your System is going use as a router for 172.24.0.0/16 and 172.25.0.0/16. Enable the IP Forwarding.

- * 1. echo "1" >/proc/sys/net/ipv4/ip_forward
- * 2. vi /etc/sysctl.conf net.ipv4.ip_forward=1

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

/proc is the virtual filesystem, containing the information about the running kernel.

To change the parameter of running kernel you should modify on /proc. From Next reboot the system, kernel will take the value from /etc/sysctl.conf.

NEW QUESTION 70

CORRECT TEXT

Copy /etc/fstab to /var/tmp name admin, the user1 could read, write and modify it, while user2 without any permission.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
# cp /etc/fstab /var/tmp/  
# chgrp admin /var/tmp/fstab  
# setfacl -m u:user1:rwX /var/tmp/fstab  
# setfacl -m u:user2:--- /var/tmp/fstab  
# ls -l  
-rw-rw-r--+ 1 root admin 685 Nov 10 15:29 /var/tmp/fstab
```

NEW QUESTION 71

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual EX200 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the EX200 Product From:

<https://www.2passeasy.com/dumps/EX200/>

Money Back Guarantee

EX200 Practice Exam Features:

- * EX200 Questions and Answers Updated Frequently
- * EX200 Practice Questions Verified by Expert Senior Certified Staff
- * EX200 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * EX200 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year