

1z0-808 Dumps

Java SE 8 Programmer I

<https://www.certleader.com/1z0-808-dumps.html>



NEW QUESTION 1

Given:

```
public static void main(String[] args) {  
    String ta = "A ";  
    ta = ta.concat("B ");  
    String tb = "C ";  
    ta = ta.concat(tb);  
    ta.replace('C', 'D');  
    ta = ta.concat(tb);  
    System.out.println(ta);  
}
```

What is the result?

- A. A B C D
- B. A C D
- C. A C D D
- D. A B D
- E. A B D C

Answer: C**NEW QUESTION 2**

Given the code fragments:

```
class Student {  
    String name;  
    int age;  
}
```

And:

```
4. public class Test {  
5.     public static void main(String[] args) {  
6.         Student s1 = new Student();  
7.         Student s2 = new Student();  
8.         Student s3 = new Student();  
9.         s1 = s3;  
10.        s3 = s2;  
11.        s2 = null;  
12.    }  
13. }
```

Which statement is true?

- A. After line 11, three objects are eligible for garbage collection.
- B. After line 11, two objects are eligible for garbage collection.
- C. After line 11, one object is eligible for garbage collection.
- D. After line 11, none of the objects are eligible for garbage collection.

Answer: C**NEW QUESTION 3**

Given the following classes:

```
public class Employee {
    public int salary;
}

public class Manager extends Employee {
    public int budget;
}

public class Director extends Manager {
    public int stockOptions;
}
```

And given the following main method:

```
public static void main(String[] args) {
    Employee employee = new Employee();
    Manager manager = new Manager();
    Director director = new Director();
    //line n1
}
```

Which two options fail to compile when placed at line n1 of the main method? (Choose two.)

- A. employee.salary = 50_000;
- B. director.salary = 80_000;
- C. employee.budget = 200_000;
- D. manager.budget = 1_000_000;
- E. manager.stockOption = 500;
- F. director.stockOptions = 1_000;

Answer: CE

NEW QUESTION 4

Given the code fragment:

```
public static void main (String[] args) {
    String[] arr = ("Hi", "How", "Are", "You");
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {
        System.out.println(s + "removed")
    }
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

Answer: A

NEW QUESTION 5

Given:

```
public class Test {
    public static void main(String[] args) {
        int x = 1;
        int y = 0;
        if(x++ > ++y) {
            System.out.print("Hello ");
        } else {
            System.out.print("Welcome ");
        }
        System.out.print("Log " + x + ":" + y);
    }
}
```

What is the result?

- A. Hello Log 1:0
- B. Hello Log 2:1
- C. Welcome Log 2:1
- D. Welcome Log 1:0

Answer: C

NEW QUESTION 6

Given the code fragment:

```
int x = 100;
int a = x++;
int b = ++x;
int c = x++;
int d = (a < b) ? (a < c) ? a : (b < c) ? b : c : x;
System.out.println(d);
```

What is the result?

- A. 100
- B. 101
- C. 102
- D. 103
- E. Compilation fails

Answer: E

NEW QUESTION 7

Given this code for a Planet object:

```
public class Planet {
    public String name;
    public int moons;

    public Planet(String name, int moons) {
        this.name = name;
        this.moons = moons;
    }
}
```

And this method:

```
public static void main(String[] args){
    Planet[] planets = {
        new Planet("Mercury", 0),
        new Planet("Venus", 0),
        new Planet("Earth", 1),
        new Planet("Mars", 2)
    };

    System.out.println(planets);
    System.out.println(planets[2].name);
    System.out.println(planets[2].moons);
}
```

What is the output?

A

```
planets
Earth
1
```

B

```
[LPlanets.Planet;@15db9742
Earth
1
```

C

```
[LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
1
```

D

```
[LPlanets.Planet;@15db9742
Planets.Planet@6d06d69c
[LPlanets.Moon;@7852e922
```

E

```
[LPlanets.Planet;@15db9742
Venus
0
```

- A. Option A
B. Option B
C. Option C
D. Option D
E. Option E

Answer: C

NEW QUESTION 8

Which two class definitions fail to compile? (Choose two.)

A

```
abstract class A3 {
    private static int i;
    public void doStuff() {}
    public A3() {}
}
```

B

```
final class A1 {
    public A1() {}
}
```

C

```
private class A2 {
    private static int i;
    private A2() {}
}
```

D

```
class A4 {
    protected static final int i = 10;
    private A4() {}
}
```

E

```
final abstract class A5 {  
    protected static int i;  
    void doStuff() {}  
    abstract void doIt();  
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: CD

NEW QUESTION 9

Given the code fragment:

```
public class Employee {  
    String name;  
    boolean contract;  
    double salary;  
    Employee() {  
        // line n1  
    }  
    public String toString() {  
        return name + ":" + contract + ":" + salary;  
    }  
    public static void main(String[] args) {  
        Employee e = new Employee();  
        // line n2  
        System.out.print(e);  
    }  
}
```

Which two modifications, when made independently, enable the code to print Joe:true: 100.0? (Choose two.)

- ☐ A) Replace line n2 with:
 e.name = "Joe";
 e.contract = true;
 e.salary = 100;
- ☐ B) Replace line n2 with:
 this.name = "Joe";
 this.contract = true;
 this.salary = 100;
- ☐ C) Replace line n1 with:
 this.name = new String("Joe");
 this.contract = new Boolean(true);
 this.salary = new Double(100);
- ☐ D) Replace line n1 with:
 name = "Joe";
 contract = TRUE;
 salary = 100.0f;
- ☐ E) Replace line n1 with:
 this("Joe", true, 100);

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: AC

NEW QUESTION 10

Given the code fragment:


```
LocalDateTime dt = LocalDateTime.of(2014, 7, 31, 1, 1);  
dt.plusDays(30);  
dt.plusMonths(1);  
System.out.println(dt.format(DateTimeFormatter.ISO_DATE_TIME));
```

What is the result?

- A. An exception is thrown at runtime
- B. 2014-07-31T01:01:00
- C. 2014-07-31
- D. 2014-09-30T00:00:00

Answer: B

NEW QUESTION 10

Given:

```
class A {  
    public void test() {  
        System.out.println("A ");  
    }  
}  
  
class B extends A {  
    public void test() {  
        System.out.println("B ");  
    }  
}  
  
public class C extends A {  
    public void test() {  
        System.out.println("C ");  
    }  
  
    public static void main(String[] args) {  
        A b1 = new A();  
        A b2 = new C();  
        A b3 = (B) b2;           //line n1  
        b1 = (A) b2;             //line n2  
        b1.test();  
        b3.test();  
    }  
}
```

What is the result?

- A. AB
- B. AC
- C. CC
- D. A ClassCastException is thrown only at line n1.
- E. A ClassCastException is thrown only at line n2.

Answer: D

NEW QUESTION 12

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 01, 32);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10
- B. 2012-02-11
- C. Compilation fails
- D. A DateTimeException is thrown at runtime.

Answer: D

NEW QUESTION 15

Given:

```
class Caller {  
    private void init () {  
        System.out.println("Initialized");  
    }  
  
    private void start () {  
        init();  
        System.out.println("Started");  
    }  
}  
  
public class TestCall {  
    public static void main(String[] args) {  
        Caller c = new Caller();  
        c.start(); // line n1  
        c.init();  // line n2  
    }  
}
```

What is the result?

- A. Compilation fails at line n1.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails at line n2.

Answer: D

NEW QUESTION 20

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 1, 30);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10
- B. 2012-01-30
- C. 2012-02-10 00:00
- D. A DateTimeException is thrown at runtime.

Answer: C

NEW QUESTION 23

Which two code fragments cause a compilation error? (Choose two.)

- A. float flt = 100.00F;
- B. float flt = (float) 1_11.00;
- C. Float flt = 100.00;
- D. double y1 = 203.22;float flt = y1;
- E. int y2 = 100;float flt = (float) y2 ;

Answer: AD

NEW QUESTION 24

Which three are advantages of the Java exception mechanism? (Choose three.)

- A. Improves the program structure because the error handling code is separated from the normal program function
- B. Provides a set of standard exceptions that covers all possible errors
- C. Improves the program structure because the programmer can choose where to handle exceptions
- D. Improves the program structure because exceptions must be handled in the method in which they occurred
- E. Allows the creation of new exceptions that are customized to the particular program being created

Answer: ACE

NEW QUESTION 25

Given this class:


```
public class Rectangle {
    private double length;
    private double height;
    private double area;

    public void setLength(double length) {
        this.length = length;
    }
    public void setHeight(double height) {
        this.height = height;
    }
    public void setArea() {
        area = length*height;
    }
}
```

Which two changes would encapsulate this class and ensure that the area field is always equal to length * height whenever the Rectangle class is used?

- A. Call the setArea method at the end of the setHeight method.
- B. Call the setArea method at the beginning of the setHeight method.
- C. Call the setArea method at the end of the setLength method.
- D. Call the setArea method at the beginning of the setLength method.
- E. Change the setArea method to private.
- F. Change the area field to public.

Answer: AE

NEW QUESTION 26

Given:

```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start();
        c.init();
    }
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails.

Answer: D

NEW QUESTION 28

Which three statements describe the object-oriented features of the Java language? (Choose three.)

- A. Objects cannot be reused.
- B. A subclass must override the methods from a superclass.
- C. Objects can share behaviors with other objects.
- D. A package must contain a main class.
- E. Object is the root class of all other objects.
- F. A main method must be declared in every class.

Answer: BCF

NEW QUESTION 29

Given:

```
class Vehicle {
    int x;
    Vehicle() {
        this(10); // line n1
    }
    Vehicle(int x) {
        this.x = x;
    }
}

class Car extends Vehicle {
    int y;
    Car() {
        super();
        this(20); // line n2
    }
    Car(int y) {
        this.y = y;
    }
    public String toString() {
        return super.x + ":" + this.y;
    }
}
```

And given the code fragment:

And given the code fragment:

```
Vehicle y = new Car();
System.out.println(y);
```

What is the result?

- A. 10:20
- B. 0:20
- C. Compilation fails at line n1
- D. Compilation fails at line n2

Answer: D

NEW QUESTION 34

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-808 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-808-dumps.html>